



Technical White Paper – ACR Assist

Proposed Format for Specifying Point-of-Care Computer-Assisted Reporting/Decision Support Modules for Radiologists

Tarik K. Alkasab, MD, PhD; Harlan B. Harvey, MD, JD; Sepehr Sadeghi; Sujith Surendran
Nair Latha

Version 1.0
October 12, 2016



1891 Preston White Drive, Reston, VA 20191

CONTENTS

| | | |
|-------|--------------------------|----|
| 1 | INTRODUCTION | 3 |
| 1.1 | Purpose | 3 |
| 2 | Representation..... | 3 |
| 2.1 | Colour patterns..... | 3 |
| 2.2 | Datatypes | 3 |
| 3 | Schema structure | 4 |
| 3.1 | Metadata | 4 |
| 3.1.1 | Sample..... | 7 |
| 3.1.2 | Real-world Sample | 9 |
| 3.2 | DataElements..... | 10 |
| 3.2.1 | ChoiceDataElement..... | 11 |
| 3.2.2 | NumericDataElement..... | 15 |
| 3.2.3 | IntegerDataElement..... | 17 |
| 3.2.4 | GlobalValue | 19 |
| 3.2.5 | MultichoiceElement | 19 |
| 3.2.6 | ComputedElement | 25 |
| 3.3 | Rules..... | 31 |
| 3.3.1 | Sample..... | 34 |
| 3.3.2 | Real-world Sample | 35 |
| 3.4 | Endpoints | 48 |
| 3.4.1 | Sample..... | 54 |
| 3.4.2 | Real-world Sample | 55 |

1 INTRODUCTION

1.1 Purpose

Explains the following

Schema structure

Description about each elements and attributes with their datatypes

Usage with samples

2 REPRESENTATION

2.1 Colour patterns

Here is the representation style for each component in the schema.

Attributes: sample

Elements: sample

Optional: sample (optional)

2.2 Datatypes

xsd:token - <https://www.w3.org/TR/xmlschema-2/#token>

xsd:anyURI - <https://www.w3.org/TR/xmlschema-2/#anyURI>

xsd:nonNegativeInteger - <https://www.w3.org/TR/xmlschema-2/#nonNegativeInteger>

xsd:integer - <https://www.w3.org/TR/xmlschema-2/#integer>

xsd:ID - <https://www.w3.org/TR/xmlschema-2/#ID>

xsd:Boolean - <https://www.w3.org/TR/xmlschema-2/#boolean>

xsd:decimal - <https://www.w3.org/TR/xmlschema-2/#decimal>

xsd: IDREF - <https://www.w3.org/TR/xmlschema-2/#IDREF>xsd:positiveInteger - <https://www.w3.org/TR/xmlschema-2/#positiveInteger>xsd:duration - <https://www.w3.org/TR/xmlschema-2/#duration>

3 SCHEMA STRUCTURE

3.1 Metadata

The metadata section contains general information about a CAR/DS guideline which may or may not be used by any given implementation.

| # | Name | Data Type | Description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------|--|------------------|--|-------|------------------------|------------------|--|-------|--|------------|--|-------|---------------------|-----------|--|-------|----------------|------------|---|-------|------|--|---|-----|--|--|---|-------|-----------------------|------------------|--|-------|-----------------|---------|---|
| 1 | Label | text | Name of the XML | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | ID | text | XML module's unique identifier | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | SchemaVersion | text | Schema version | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | RuleVersion | text | Module version. This can be updated each time when the xml has modified. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | Info(optional) | | <table border="1"> <tr> <td>5.1</td><td>Description (optional)</td><td>text</td><td>Human readable description about the module.</td></tr> <tr> <td>5.2</td><td>References (optional) Contains one or more Citations. Citation</td><td></td><td> <table border="1"> <tr> <td>5.2.1</td><td>PubmedId (optional)</td><td>xsd:token</td><td>Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed</td></tr> <tr> <td>5.2.2</td><td>URI (optional)</td><td>xsd:anyURI</td><td>Any Reference URI (for e.g.: link to abstract on journal website)</td></tr> <tr> <td>5.2.3</td><td>text</td><td></td><td>citation text (for e.g. : a bibliographic reference to the citation)</td></tr> </table> </td></tr> <tr> <td>5.3</td><td>Diagrams (optional) Contains different Diagrams related to the module. Diagram</td><td></td><td> <table border="1"> <tr> <td>5.3.1</td><td>KeyDiagram (optional)</td><td>"true" "false"</td><td>Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram)</td></tr> <tr> <td>5.3.2</td><td>Displaysequence</td><td>Integer</td><td>Image display sequence number. Images can</td></tr> </table> </td></tr> </table> | 5.1 | Description (optional) | text | Human readable description about the module. | 5.2 | References (optional) Contains one or more Citations. Citation | | <table border="1"> <tr> <td>5.2.1</td><td>PubmedId (optional)</td><td>xsd:token</td><td>Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed</td></tr> <tr> <td>5.2.2</td><td>URI (optional)</td><td>xsd:anyURI</td><td>Any Reference URI (for e.g.: link to abstract on journal website)</td></tr> <tr> <td>5.2.3</td><td>text</td><td></td><td>citation text (for e.g. : a bibliographic reference to the citation)</td></tr> </table> | 5.2.1 | PubmedId (optional) | xsd:token | Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed | 5.2.2 | URI (optional) | xsd:anyURI | Any Reference URI (for e.g.: link to abstract on journal website) | 5.2.3 | text | | citation text (for e.g. : a bibliographic reference to the citation) | 5.3 | Diagrams (optional) Contains different Diagrams related to the module. Diagram | | <table border="1"> <tr> <td>5.3.1</td><td>KeyDiagram (optional)</td><td>"true" "false"</td><td>Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram)</td></tr> <tr> <td>5.3.2</td><td>Displaysequence</td><td>Integer</td><td>Image display sequence number. Images can</td></tr> </table> | 5.3.1 | KeyDiagram (optional) | "true" "false" | Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram) | 5.3.2 | Displaysequence | Integer | Image display sequence number. Images can |
| 5.1 | Description (optional) | text | Human readable description about the module. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.2 | References (optional) Contains one or more Citations. Citation | | <table border="1"> <tr> <td>5.2.1</td><td>PubmedId (optional)</td><td>xsd:token</td><td>Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed</td></tr> <tr> <td>5.2.2</td><td>URI (optional)</td><td>xsd:anyURI</td><td>Any Reference URI (for e.g.: link to abstract on journal website)</td></tr> <tr> <td>5.2.3</td><td>text</td><td></td><td>citation text (for e.g. : a bibliographic reference to the citation)</td></tr> </table> | 5.2.1 | PubmedId (optional) | xsd:token | Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed | 5.2.2 | URI (optional) | xsd:anyURI | Any Reference URI (for e.g.: link to abstract on journal website) | 5.2.3 | text | | citation text (for e.g. : a bibliographic reference to the citation) | | | | | | | | | | | | | | | | | | | | |
| 5.2.1 | PubmedId (optional) | xsd:token | Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.2.2 | URI (optional) | xsd:anyURI | Any Reference URI (for e.g.: link to abstract on journal website) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.2.3 | text | | citation text (for e.g. : a bibliographic reference to the citation) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.3 | Diagrams (optional) Contains different Diagrams related to the module. Diagram | | <table border="1"> <tr> <td>5.3.1</td><td>KeyDiagram (optional)</td><td>"true" "false"</td><td>Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram)</td></tr> <tr> <td>5.3.2</td><td>Displaysequence</td><td>Integer</td><td>Image display sequence number. Images can</td></tr> </table> | 5.3.1 | KeyDiagram (optional) | "true" "false" | Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram) | 5.3.2 | Displaysequence | Integer | Image display sequence number. Images can | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.3.1 | KeyDiagram (optional) | "true" "false" | Is it the key diagram (I.e. the diagram which summarizes whether this is the overall clinical diagram) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.3.2 | Displaysequence | Integer | Image display sequence number. Images can | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | |
|---------|--|--|---------------------|--|---------|------|-----------|---------------------|---------|------|--|-------------|
| | | (optional) | | be displayed in Displaysequence order | | | | | | | | |
| | 5.3.3 | Location | URI | Image URI | | | | | | | | |
| | 5.3.4 | Label (optional) | text | Image Label | | | | | | | | |
| | 5.4 | HelpText(optional) | text | Help text about the module. | | | | | | | | |
| | 5.5 | Contact(optional) | | | | | | | | | | |
| | 5.5.1 | Name | text | Author/Contact Name | | | | | | | | |
| | 5.5.2 | Email | text | Contact Email | | | | | | | | |
| | 5.5.3 | Institution(optional) | text | Contact Institution | | | | | | | | |
| 6 | ReportCitationText | | text | Citation for the report text | | | | | | | | |
| 7 | Ontology(optional) Specify body part and modality (like CT-Chest, MR-abdomen) of the imaging exams for which this module can be used | | | | | | | | | | | |
| | 7.1 | AnatomicRegions AnatomicRegions for which this module can be applicable e.g. : <pre><AnatomicRegions codingSystemAttr="RADLEX"> <Region Code="RID88">Adrenal gland</Region> <Region Code="RID89">Limb of adrenal gland</Region> <Region Code="RID90">Medulla of adrenal gland</Region> </AnatomicRegions></pre> | | | | | | | | | | |
| | 7.1.1 | codingSystemAttr (optional) | text | The source of coding system used. This should be a URL | | | | | | | | |
| | 7.1.2 | Region <table border="1"> <tr> <td>7.1.2.1</td><td>Code</td><td>xsd:token</td><td>Author/Contact Name</td></tr> <tr> <td>7.1.2.2</td><td>Text</td><td></td><td>Region text</td></tr> </table> | | | 7.1.2.1 | Code | xsd:token | Author/Contact Name | 7.1.2.2 | Text | | Region text |
| 7.1.2.1 | Code | xsd:token | Author/Contact Name | | | | | | | | | |
| 7.1.2.2 | Text | | Region text | | | | | | | | | |
| | 7.2 | PossibleDiagnoses For e.g. : <pre><PossibleDiagnoses> <Diagnosis CodingSystem="ICD-10" Code="E27.9">Disorder of adrenal gland, unspecified</Diagnosis> <Diagnosis CodingSystem="RADLEX" Code="RID4211">Adenoma</Diagnosis> <Diagnosis CodingSystem="RADLEX" Code="RID4353">Myelolipoma</Diagnosis> <Diagnosis CodingSystem="RADLEX" Code="RID3890">Cyst</Diagnosis></pre> | | | | | | | | | | |

| | | | | | | | | | | | | | |
|---------------|--|--|--|----------------------------------|------|----------------------|----------------------------|------------------------|--|----------------------|-------------------------|--------------------|--------------------------|
| | <pre><Diagnosis CodingSystem="RADLEX" Code="RID4700">Hemorrhage</Diagnosis> <Diagnosis CodingSystem="RADLEX" Code="RID5231">Metastasis</Diagnosis> </PossibleDiagnoses></pre> | | | | | | | | | | | | |
| | 7.2.1 | CodingSystem (optional) | text | the source of coding system used | | | | | | | | | |
| | 7.2.2 | Diagnosis can contain one or more diagnosis <table border="1"> <tr> <td>7.2.2.1. 1</td><td>CodingSystem (optional)</td><td>text</td><td>The source of coding system used. This should be a URL</td></tr> <tr> <td>7.2.2.1. 2</td><td>Code</td><td>xsd:token</td><td>Code in coding system</td></tr> </table> | | | | 7.2.2.1. 1 | CodingSystem (optional) | text | The source of coding system used. This should be a URL | 7.2.2.1. 2 | Code | xsd:token | Code in coding system |
| 7.2.2.1. 1 | CodingSystem (optional) | text | The source of coding system used. This should be a URL | | | | | | | | | | |
| 7.2.2.1. 2 | Code | xsd:token | Code in coding system | | | | | | | | | | |
| 8 | ApplicableExams (optional) contains one or more ApplicableExamCategory <pre><ApplicableExams> <ApplicableExamCategory Axis="Modality">CT</ApplicableExamCategory> <ApplicableExamCategory Axis="Anatomy">Chest</ApplicableExamCategory> <ApplicableExamCategory Axis="Anatomy">Abdomen</ApplicableExamCategory> </ApplicableExams></pre> | | | | | | | | | | | | |
| | 8.1 | ApplicableExamCategory <table border="1"> <tr> <td>8.1.1</td><td>Axis</td><td>"Modality" "Anatomy"</td><td>Value can either Modality or Anatomy</td></tr> <tr> <td>8.1.2</td><td>text</td><td></td><td>Applicable category text</td></tr> </table> | | | | 8.1.1 | Axis | "Modality" "Anatomy" | Value can either Modality or Anatomy | 8.1.2 | text | | Applicable category text |
| 8.1.1 | Axis | "Modality" "Anatomy" | Value can either Modality or Anatomy | | | | | | | | | | |
| 8.1.2 | text | | Applicable category text | | | | | | | | | | |
| 9 | ApplicableSexes <table border="1"> <tr> <td>9.1</td><td>Value</td><td>"Male" "Female" "Both"</td><td>Applicable sex</td></tr> </table> | | | | 9.1 | Value | "Male" "Female" "Both" | Applicable sex | | | | | |
| 9.1 | Value | "Male" "Female" "Both" | Applicable sex | | | | | | | | | | |
| 10 | ApplicableAgeGroups (optional) <table border="1"> <tr> <td>10.1</td><td>MinimumAge(optional)</td><td>xsd:nonNegative Integer</td><td>applicable age min</td></tr> <tr> <td>10.2</td><td>MaximumAge(optional)</td><td>xsd:nonNegative Integer</td><td>applicable age max</td></tr> </table> | | | | 10.1 | MinimumAge(optional) | xsd:nonNegative Integer | applicable age min | 10.2 | MaximumAge(optional) | xsd:nonNegative Integer | applicable age max | |
| 10.1 | MinimumAge(optional) | xsd:nonNegative Integer | applicable age min | | | | | | | | | | |
| 10.2 | MaximumAge(optional) | xsd:nonNegative Integer | applicable age max | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------|---|--------|--|-------------------------|-----------------------------|--|--------|--|------|----------------------------|------|--|--------|----------------|------|-----------------------------|------|--|--------|-----------------------|--|--------------------------|------|-------------------------|------|--|-------------------------|
| 11 | <p>TextCues</p> <table border="1"> <tr> <td>11.1</td><td>ContextPhrases(optional) Context phrases used to identify parts of the radiology reports where this module may be applicable.</td><td>11.1.1</td><td>ContextPhrase</td><td>text</td><td>phrase to find out the xml</td></tr> </table> <table border="1"> <tr> <td>11.2</td><td>KeyWords Keywords to find the module</td><td>11.2.1</td><td>Keyword</td><td>text</td><td>Keywords to find out module</td></tr> </table> <table border="1"> <tr> <td>11.3</td><td>NegationPhrases(optional) Contains text markers which indicate the parts of a report to which the module is not applicable (even though it may contain markers that make it look like it is).</td><td>11.3.1</td><td>NegationPhrase</td><td></td><td>Keywords to find out xml</td></tr> </table> <table border="1"> <tr> <td>11.4</td><td>Regex(optional)</td><td>text</td><td></td><td>Regex matches with test</td></tr> </table> | | | | 11.1 | ContextPhrases (optional) Context phrases used to identify parts of the radiology reports where this module may be applicable. | 11.1.1 | ContextPhrase | text | phrase to find out the xml | 11.2 | KeyWords Keywords to find the module | 11.2.1 | Keyword | text | Keywords to find out module | 11.3 | NegationPhrases (optional) Contains text markers which indicate the parts of a report to which the module is not applicable (even though it may contain markers that make it look like it is). | 11.3.1 | NegationPhrase | | Keywords to find out xml | 11.4 | Regex (optional) | text | | Regex matches with test |
| 11.1 | ContextPhrases (optional) Context phrases used to identify parts of the radiology reports where this module may be applicable. | 11.1.1 | ContextPhrase | text | phrase to find out the xml | | | | | | | | | | | | | | | | | | | | | | |
| 11.2 | KeyWords Keywords to find the module | 11.2.1 | Keyword | text | Keywords to find out module | | | | | | | | | | | | | | | | | | | | | | |
| 11.3 | NegationPhrases (optional) Contains text markers which indicate the parts of a report to which the module is not applicable (even though it may contain markers that make it look like it is). | 11.3.1 | NegationPhrase | | Keywords to find out xml | | | | | | | | | | | | | | | | | | | | | | |
| 11.4 | Regex (optional) | text | | Regex matches with test | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | <p>VoiceActivation(optional) Contains phrases intended to be used as triggers for the module to find by voice recognition systems.</p> <table border="1"> <tr> <td>12.1</td><td>VoiceCommandPhrase</td><td>text</td><td>The voice activation phrase for the voice recognition system to find the module.</td></tr> </table> | | | | 12.1 | VoiceCommandPhrase | text | The voice activation phrase for the voice recognition system to find the module. | | | | | | | | | | | | | | | | | | | |
| 12.1 | VoiceCommandPhrase | text | The voice activation phrase for the voice recognition system to find the module. | | | | | | | | | | | | | | | | | | | | | | | | |

3.1.1 Sample

```
<Metadata>
  <Label>Label0</Label>
  <ID>ID0</ID>
  <SchemaVersion>SchemaVersion0</SchemaVersion>
  <RuleVersion>RuleVersion0</RuleVersion>
  <Info>
    <Description>Description0</Description>
    <References>
      <Citation PubmedId="PubmedId0" Url="http://www.url.com/">
      </Citation>
      <Citation PubmedId="PubmedId1" Url="http://www.url.com/">
      </Citation>
      <Citation PubmedId="PubmedId2" Url="http://www.url.com/">
      </Citation>
```

```
<Citation PubmedId="PubmedId3" Url="http://www.url.com/">
</Citation>
</References>
<Diagrams>
<Diagram KeyDiagram="true" DisplaySequence="0">
<imageElements>http://www.url.com/</imageElements>
<Label>Label1</Label>
</Diagram>
<Diagram KeyDiagram="true" DisplaySequence="0">
<imageElements>http://www.url.com/</imageElements>
<Label>Label2</Label>
</Diagram>
</Diagrams>
<HelpText>HelpText0</HelpText>
<Contact>
<Name>Name</Name>
<Email>Email</Email>
<Institution>Institution</Institution>
</Contact>
</Info>
<ReportCitationText>ReportCitationText0</ReportCitationText>
<Ontology>
<AnatomicRegions codingSystemAttr="codingSystemAttr0">
<Region Code="Code0">
</Region>
<Region Code="Code1">
</Region>
</AnatomicRegions>
<AnatomicRegions codingSystemAttr="codingSystemAttr1">
<Region Code="Code2">
</Region>
<Region Code="Code3">
</Region>
</AnatomicRegions>
<PossibleDiagnoses CodingSystem="CodingSystem0">
<Diagnosis CodingSystem="CodingSystem1" Code="Code4">
</Diagnosis>
<Diagnosis CodingSystem="CodingSystem2" Code="Code5">
</Diagnosis>
</PossibleDiagnoses>
<PossibleDiagnoses CodingSystem="CodingSystem3">
<Diagnosis CodingSystem="CodingSystem4" Code="Code6">
</Diagnosis>
<Diagnosis CodingSystem="CodingSystem5" Code="Code7">
</Diagnosis>
</PossibleDiagnoses>
</Ontology>
<ApplicableExams>
<ApplicableExamCategory Axis="Modality">
</ApplicableExamCategory>
<ApplicableExamCategory Axis="Modality">
</ApplicableExamCategory>
```

```

</ApplicableExams>
<ApplicableSexes Value="Male"/>
<ApplicableAgeGroups>
  <MinimumAge>50</MinimumAge>
  <MaximumAge>50</MaximumAge>
</ApplicableAgeGroups>
<TextCues>
  <ContextPhrases>
    <ContextPhrase>ContextPhrase0</ContextPhrase>
    <ContextPhrase>ContextPhrase1</ContextPhrase>
  </ContextPhrases>
  <KeyWords>
    <KeyWord>KeyWord0</KeyWord>
    <KeyWord>KeyWord1</KeyWord>
  </KeyWords>
  <NegationPhrases>
    <NegationPhrase>NegationPhrase0</NegationPhrase>
    <NegationPhrase>NegationPhrase1</NegationPhrase>
  </NegationPhrases>
  <Regex>Regex0</Regex>
</TextCues>
<VoiceActivation>
  <VoiceCommandPhrase>VoiceCommandPhrase0</VoiceCommandPhrase>
  <VoiceCommandPhrase>VoiceCommandPhrase1</VoiceCommandPhrase>
</VoiceActivation>
</Metadata>

```

3.1.2 Real-world Sample

```

<Metadata>
  <Label>Hello RADS</Label>
  <ID>Hello_Rads_1_0</ID>
  <SchemaVersion>1.0</SchemaVersion>
  <RuleVersion>1.6</RuleVersion>
  <Info>
    <Description>This is a sample xml for characterizing liver lesion for MRI</Description>
    <References>
      <Citation Url="https://nrdr.acr.org/lirads/">
      </Citation>
      <Citation Url="https://nrdr.acr.org/liradsapp/">
      </Citation>
    </References>
    <Diagrams>
      <Diagram DisplaySequence="1" KeyDiagram="true">
        <imageElements>https://nrdr.acr.org/lirads/ </imageElements>
        <Label>ACR LI-RADS</Label>
      </Diagram>
    </Diagrams>
    <Contact>
      <Name>ACR Assist</Name>
      <Email>acr-assist@acr.org</Email>
    </Contact>
  </Info>
</Metadata>

```

```

<Institution>American College of Radiology</Institution>
</Contact>
</Info>
<ReportCitationText/>
<Ontology>
  <AnatomicRegions>
    <Region Code=""></Region>
  </AnatomicRegions>
  <PossibleDiagnoses>
    <Diagnosis Code=""></Diagnosis>
  </PossibleDiagnoses>
</Ontology>
<ApplicableExams>
  <ApplicableExamCategory Axis="Modality">
  </ApplicableExamCategory>
  <ApplicableExamCategory Axis="Anatomy"/>
</ApplicableExams>
<ApplicableSexes Value="Both"></ApplicableSexes>
<ApplicableAgeGroups>
  <MinimumAge>1</MinimumAge>
</ApplicableAgeGroups>
<TextCues>
  <ContextPhrases>
    <ContextPhrase></ContextPhrase>
  </ContextPhrases>
  <KeyWords>
    <KeyWord>LIRADS Liver lesion</KeyWord>
  </KeyWords>
  <NegationPhrases>
    <NegationPhrase></NegationPhrase>
  </NegationPhrases>
  <Regex/>
</TextCues>
<VoiceActivation>
  <VoiceCommandPhrase>LIRADS</VoiceCommandPhrase>
  <VoiceCommandPhrase>Liver lesion</VoiceCommandPhrase>
  <VoiceCommandPhrase>American College of Radiology</VoiceCommandPhrase>
</VoiceActivation>
</Metadata>

```

3.2 DataElements

The DataElement definitions specify the input values used to drive a decision tree, the constant values, and possibly intermediate or output values associated with an algorithm. Three main types of DataElements can be described using the data format: external and fixed values, user-provided data, and results of computation. Schema supports the following DataElements.

Following are the different DataElements supported by the schema

- ChoiceDataElement : can be used when there is a pre-defined set of answers are available
- NumericDataElement : represents a number
- IntegerDataElement : represents an integer value
- MultiChoiceDataElement: can be used when there is a pre-defined set of answers and can have one or more answers.
- GlobalValue: similar to constants in any programming language that can be referred to elsewhere in the guideline. These are intended to be used to define threshold values or parameters in a linear regression.
- ComputedElement: effective when it comes to reusing the logic

3.2.1 ChoiceDataElement

| # | Name | Data Type | Description / Usage | | | | | | | | | | | | | | | | | | | | |
|-------|---|--|--|-----|----------------|--|--|-------|-----------------|------|----------------|-------|--------------|------|-------------|-------|-----------------------------------|-------------|--|-------|------------------------------|------------------|---------------------------------|
| 1. | Id | xsd:ID | DataElement identifier (can be referenced in other parts of module as well as by external systems) | | | | | | | | | | | | | | | | | | | | |
| 2 | Cdeld (optional) | xsd:token | Common DataElement Id (intend to refer a standard definition in the ACR/RSNA CDE repository, radelement.org) | | | | | | | | | | | | | | | | | | | | |
| 3 | IsRequired | "true" "false" | Whether the DataElement is Required or not. | | | | | | | | | | | | | | | | | | | | |
| 4 | DisplaySequence (optional) | xsd:integer | Suggested order in which this DataElement is displayed together with the other DataElements | | | | | | | | | | | | | | | | | | | | |
| 5 | Label | text | Choice DataElement label (prompt text/display question for entering the value) | | | | | | | | | | | | | | | | | | | | |
| 6 | Hint (optional) | text | Optionally displayed more detailed text for the user describing how the DataElement needs to be filled in. | | | | | | | | | | | | | | | | | | | | |
| 7 | diagrams (optional) Contains one or more diagrams which offer additional information to the user (e.g.: illustrations of how the measurements are to be taken) | <table border="1"> <tr> <td>7.1</td> <td>diagram</td> <td></td> <td></td> </tr> <tr> <td>7.1.1</td> <td>Location</td> <td>text</td> <td>Image location</td> </tr> <tr> <td>7.1.2</td> <td>Label</td> <td>text</td> <td>Image Label</td> </tr> <tr> <td>7.1.3</td> <td>DisplaySequence(optional)</td> <td>xsd:integer</td> <td>Image display sequence if the DataElement contains more than one diagram</td> </tr> <tr> <td>7.1.4</td> <td>KeyDiagram(optional)</td> <td>"true" "false"</td> <td>Whether this is the key diagram</td> </tr> </table> | | 7.1 | diagram | | | 7.1.1 | Location | text | Image location | 7.1.2 | Label | text | Image Label | 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram |
| 7.1 | diagram | | | | | | | | | | | | | | | | | | | | | | |
| 7.1.1 | Location | text | Image location | | | | | | | | | | | | | | | | | | | | |
| 7.1.2 | Label | text | Image Label | | | | | | | | | | | | | | | | | | | | |
| 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | | | | | | | | | | | | | | | | | | | | |
| 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------|--|-----------------------------|---|--------|--------------|-----------|--------------|-------|--------------|------|---|-------|------------------------|------|---|-------|--------------------------------|------|--|-------|----------------|------------------|---|-------|------------------------------|------|---|
| 8 | VoiceCommand (optional) | text | Voice command to find/activate the DataElement | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | ChoiceInfo Contains all the possible values for the DataElement, only one value can be selected for a choice DataElement (for questions with multiple choice please use the MultiChoiceDataElement) | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1 | Choice <table border="1"> <tr> <td>9.1.1</td><td>Value</td><td>xsd:token</td><td>Choice value</td></tr> <tr> <td>9.1.2</td><td>Label</td><td>text</td><td>Choice label (how the choice is intended to be displayed for the user in the GUI)</td></tr> <tr> <td>9.1.3</td><td>Hint (optional)</td><td>text</td><td>Further information on the choice which can be optional (e.g.: as a tooltip)</td></tr> <tr> <td>9.1.4</td><td>VoiceCommand (optional)</td><td>text</td><td>Voice command to select this choice as the value for the DataElement</td></tr> <tr> <td>9.1.5</td><td>Default</td><td>"true" "false"</td><td>Is this the default choice (if no other choice selected, this will be the value for the DataElement)</td></tr> <tr> <td>9.1.6</td><td>ReportText (optional)</td><td>text</td><td>Text to be inserted into the report when the DataElement value is being inserted into the report.</td></tr> </table> | | | 9.1.1 | Value | xsd:token | Choice value | 9.1.2 | Label | text | Choice label (how the choice is intended to be displayed for the user in the GUI) | 9.1.3 | Hint (optional) | text | Further information on the choice which can be optional (e.g.: as a tooltip) | 9.1.4 | VoiceCommand (optional) | text | Voice command to select this choice as the value for the DataElement | 9.1.5 | Default | "true" "false" | Is this the default choice (if no other choice selected, this will be the value for the DataElement) | 9.1.6 | ReportText (optional) | text | Text to be inserted into the report when the DataElement value is being inserted into the report. |
| 9.1.1 | Value | xsd:token | Choice value | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1.2 | Label | text | Choice label (how the choice is intended to be displayed for the user in the GUI) | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1.3 | Hint (optional) | text | Further information on the choice which can be optional (e.g.: as a tooltip) | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1.4 | VoiceCommand (optional) | text | Voice command to select this choice as the value for the DataElement | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1.5 | Default | "true" "false" | Is this the default choice (if no other choice selected, this will be the value for the DataElement) | | | | | | | | | | | | | | | | | | | | | | | | |
| 9.1.6 | ReportText (optional) | text | Text to be inserted into the report when the DataElement value is being inserted into the report. | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | ImageMap (optional) Includes a pointer to the image that can be displayed as an interactive choice/multi choice question. Areas of the images which radiologist click should select one of the given choices. Image must be provided within the assets of the module. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.1 | imageElements | xsd:anyURI | Image url pointing to the actual image location | | | | | | | | | | | | | | | | | | | | | | | | |
| | Label (optional) | text | Image Label, text used to referring the image. | | | | | | | | | | | | | | | | | | | | | | | | |
| | DrawStyle (optional) Draw style used in the image. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10.3. | Outline(optional) 1 | Default area outline color specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10.3. | HoverFill(optional) 2 | Default area fill color when hovering specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10.3. | SelectedFill(optional) 3 | Default area fill color when selected specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | |
| | Map <table border="1"> <tr> <td>10.4.1</td><td>Area</td></tr> </table> | | | 10.4.1 | Area | | | | | | | | | | | | | | | | | | | | | | |
| 10.4.1 | Area | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | |
|----------|------------------------|----------------------------|--|
| | | | Specifies region of the image to be which when selected activates a choice automatically. This has same concept as html image map, refer : http://www.w3schools.com/TAGS/tag_map.asp |
| 10.4.1.1 | Shape | "rect" "poly" "circle" | Supports three different shapes. |
| 10.4.1.2 | Coords | text | Image map coordinates |
| 10.4.1.3 | ChoiceValue | xsd:token | Choice value for this image map, which will activated when user clicks within the specified coordinates |
| 10.4.1.4 | Outline(optional) | text | Area outline color specified as hex code, which overrides the default defined in draw style |
| 10.4.1.5 | HoverFill(optional) | text | area fill color when hovering specified as hex code, which overrides the default defined in draw style |
| 10.4.1.6 | SelectedFill(optional) | text | area fill color when selected specified as hex code, which overrides the default defined in draw style |

3.2.1.1 Sample

```
<ChoiceDataElement Id="ID000" CdId="CdId0" IsRequired="true" DisplaySequence="50">
  <Label>Label0</Label>
  <Hint>Hint0</Hint>
  <Diagrams>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location0</Location>
      <Label>Label1</Label>
    </Diagram>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location1</Location>
      <Label>Label2</Label>
    </Diagram>
  </Diagrams>
  <VoiceCommand>VoiceCommand0</VoiceCommand>
```

```

<ChoiceInfo>
  <Choice Default="true">
    <Value>Value0</Value>
    <Label>Label3</Label>
    <Hint>Hint1</Hint>
    <VoiceCommand>VoiceCommand1</VoiceCommand>
    <ReportText>ReportText0</ReportText>
  </Choice>
  <Choice Default="true">
    <Value>Value1</Value>
    <Label>Label4</Label>
    <Hint>Hint2</Hint>
    <VoiceCommand>VoiceCommand2</VoiceCommand>
    <ReportText>ReportText1</ReportText>
  </Choice>
  <Choice Default="true">
    <Value>Value2</Value>
    <Label>Label5</Label>
    <Hint>Hint3</Hint>
    <VoiceCommand>VoiceCommand3</VoiceCommand>
    <ReportText>ReportText2</ReportText>
  </Choice>
</ChoiceInfo>
<ImageMap>
  <imageElements>http://www.url.com/</imageElements>
  <Label>Label6</Label>
  <DrawStyle Outline="Outline0" HoverFill="HoverFill0" SelectedFill="SelectedFill0"/>
  <Map>
    <Area Shape="rect" Coords="Coords0" ChoiceValue="ChoiceValue0" Outline="Outline1" HoverFill="HoverFill1"
SelectedFill="SelectedFill1"/>
    <Area Shape="rect" Coords="Coords1" ChoiceValue="ChoiceValue1" Outline="Outline2" HoverFill="HoverFill2"
SelectedFill="SelectedFill2"/>
  </Map>
</ImageMap>
</ChoiceDataElement>

```

3.2.1.2 Real-world Sample

```

<ChoiceDataElement Id="observationCharacter" IsRequired="true" CdId="RDE65" DisplaySequence="1">
  <Label>Observation in high risk patient</Label>
  <Hint> Observation : Area with imaging features that differ from those of adjacent liver
  parenchyma \r\n high risk patient:in whom the incidence of HCC is sufficient to justify
  screening or surveillance according to AASLD guidelines </Hint>
  <Diagrams>
    <Diagram>
      <Location>observation.png</Location>
      <Label>observation</Label>
    </Diagram>
  </Diagrams>

```

```

<VoiceCommand> Observation in high risk patient </VoiceCommand>
<ChoiceInfo>
  <Choice>
    <Value>treatedObservation</Value>
    <Label>Treated observation</Label>
    <Hint>An observation that has undergone loco-regional treatment</Hint>
  </Choice>
  <Choice>
    <Value>definitelyBenign</Value>
    <Label>Definitely benign</Label>
    <Hint> Cyst Hemangioma Vascular anomaly Perfusion alteration Hepatic fat deposition or
          sparing Hypertrophic pseudomass Confluent fibrosis Focal scar Observation that
          spontaneously disappears at follow-up</Hint>
  </Choice>
  <Choice>
    <Value>probablyBenign</Value>
    <Label>Probably benign</Label>
    <Hint>Probable benign entities (examples) Probable: Cyst Hemangioma Vascular anomaly
          Perfusion alteration Hepatic fat deposition or sparing Hypertrophic pseudomass
          Confluent fibrosis Focal scar LR-2 cirrhosis associated nodule </Hint>
  </Choice>
  <Choice>
    <Value>notDefProbBenign</Value>
    <Label>Neither definite nor probable benign</Label>
  </Choice>
  <Choice>
    <Value>notspecificforhcc</Value>
    <Label>Probable malignancy, not specific for HCC</Label>
    <Hint>Observation is probably malignant, but imaging features are not specific for
          HCC</Hint>
  </Choice>
  <Choice>
    <Value>tumorInVein</Value>
    <Label>Tumor in vein</Label>
    <Hint>Presence of tumor in vein lumen.</Hint>
  </Choice>
</ChoiceInfo>
</ChoiceDataElement>

```

3.2.2 NumericDataElement

| # | Name | Data Type | Description / Usage |
|---|-------------------------|-----------|--|
| 1 | Id | xsd:ID | DataElement identifier (can be referenced in other parts of module as well as by external systems) |
| 2 | CdeId (optional) | xsd:token | Common DataElement Id (intend to refer a standard definition in the ACR/RSNA CDE |

| | | | | | | | | | | | | | | | | | | | |
|-------|---|--|--|-----------------|------|----------------|-------|--------------|------|-------------|-------|-----------------------------------|-------------|--|-------|------------------------------|------------------|---------------------------------|--|
| | | | repository, radelement.org) | | | | | | | | | | | | | | | | |
| 3 | IsRequired | "true" "false" | Whether the DataElement is Required or not. | | | | | | | | | | | | | | | | |
| 4 | DisplaySequence (optional) | xsd:integer | Suggested order in which this DataElement is displayed together with the other DataElements | | | | | | | | | | | | | | | | |
| 5 | Label | text | Numeric DataElement label (prompt text/display question for entering the value) | | | | | | | | | | | | | | | | |
| 6 | Hint (optional) | text | Optionally displayed more detailed text for the user describing how the DataElement needs to be filled in. | | | | | | | | | | | | | | | | |
| 7 | diagrams (optional) Contains one or more diagrams which offer additional information to the user (e.g.: illustrations of how the measurements are to be taken) | 7.1 diagram <table border="1"> <tr> <td>7.1.1</td><td>Location</td><td>text</td><td>Image location</td></tr> <tr> <td>7.1.2</td><td>Label</td><td>text</td><td>Image Label</td></tr> <tr> <td>7.1.3</td><td>DisplaySequence(optional)</td><td>xsd:integer</td><td>Image display sequence if the DataElement contains more than one diagram</td></tr> <tr> <td>7.1.4</td><td>KeyDiagram(optional)</td><td>"true" "false"</td><td>Whether this is the key diagram</td></tr> </table> | 7.1.1 | Location | text | Image location | 7.1.2 | Label | text | Image Label | 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram | |
| 7.1.1 | Location | text | Image location | | | | | | | | | | | | | | | | |
| 7.1.2 | Label | text | Image Label | | | | | | | | | | | | | | | | |
| 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | | | | | | | | | | | | | | | | |
| 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram | | | | | | | | | | | | | | | | |
| 8 | VoiceCommand (optional) | text | Voice command to find/activate the DataElement | | | | | | | | | | | | | | | | |
| 9 | Minimum (optional) | xsd:decimal | Minimum allowed value | | | | | | | | | | | | | | | | |
| 10 | Maximum (optional) | xsd:decimal | Maximum allowed value | | | | | | | | | | | | | | | | |

3.2.2.1 Sample

```
<NumericDataElement Id="ID000" CdId="CdId0" IsRequired="true" DisplaySequence="50">
  <Label>Label0</Label>
  <Hint>Hint0</Hint>
  <Diagrams>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location0</Location>
      <Label>Label1</Label>
    </Diagram>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location1</Location>
      <Label>Label2</Label>
    </Diagram>
  </Diagrams>
  <VoiceCommand>VoiceCommand0</VoiceCommand>
```

```
<Minimum>0</Minimum>
<Maximum>0</Maximum>
</NumericDataElement>
```

3.2.2.2 Real-world Sample

```
<NumericDataElement Id="diameter" IsRequired="true" CdId="RDE81" DisplaySequence="3">
  <Label>Diameter (mm)</Label>
  <Hint>Size of the lesion (outer edge to outer edge) in mm</Hint>
  <Diagrams>
    <Diagram>
      <Location>diameter1.png</Location>
      <Label></Label>
    </Diagram>
    <Diagram>
      <Location>diameter2.png</Location>
      <Label></Label>
    </Diagram>
    <Diagram>
      <Location>diameter3.png</Location>
      <Label></Label>
    </Diagram>
    <Diagram>
      <Location>diameter4.png</Location>
      <Label></Label>
    </Diagram>
    <Diagram>
      <Location>diameter5.png</Location>
      <Label></Label>
    </Diagram>
  </Diagrams>
  <Minimum>1</Minimum>
</NumericDataElement>
```

3.2.3 IntegerDataElement

| # | Name | Data Type | Description / Usage |
|----|-----------------------------------|------------------|--|
| 2. | Id | xsd:ID | DataElement identifier (can be referenced in other parts of module as well as by external systems) |
| 2 | CdId (optional) | xsd:token | Common DataElement Id (intend to refer a standard definition in the ACR/RSNA CDE repository, radelement.org) |
| 3 | IsRequired | “true” “false” | Whether the DataElement is Required or not. |
| 4 | DisplaySequence (optional) | xsd:integer | Suggested order in which this DataElement is |

| | | | |
|-------|---|------------------|--|
| | | | displayed together with the other DataElements |
| 5 | Label | text | IntegerDataElement label (prompt text/display question for entering the value) |
| 6 | Hint (optional) | text | Optionally displayed more detailed text for the user describing how the DataElement needs to be filled in. |
| 7 | diagrams (optional) Contains one or more diagrams which offer additional information to the user (e.g.: illustrations of how the measurements are to be taken) | | |
| 7.1 | diagram | | |
| 7.1.1 | Location | text | Image location |
| 7.1.2 | Label | text | Image Label |
| 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram |
| 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram |
| 8 | VoiceCommand (optional) | text | Voice command to find/activate the DataElement |
| 9 | Minimum (optional) | xsd:decimal | Minimum allowed value |
| 10 | Maximum (optional) | xsd:decimal | Maximum allowed value |

3.2.3.1 Sample

```
<IntegerDataElement Id="ID000" CdId="CdId0" IsRequired="true" DisplaySequence="50">
  <Label>Label0</Label>
  <Hint>Hint0</Hint>
  <Diagrams>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location0</Location>
      <Label>Label1</Label>
    </Diagram>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location1</Location>
      <Label>Label2</Label>
    </Diagram>
  </Diagrams>
  <VoiceCommand>VoiceCommand0</VoiceCommand>
  <Minimum>0</Minimum>
```

```
<Maximum>0</Maximum>
</IntegerDataElement>
```

3.2.3.2 Real-world Sample

```
<IntegerDataElement Id="patientAge">
  <Label>Age</Label>
</IntegerDataElement>
```

3.2.4 GlobalValue

| # | Name | Data Type | Description / Usage |
|---|------|-----------|---------------------|
| 1 | Id | xsd:ID | identifier |
| 2 | text | | Value |

3.2.4.1 Sample

```
< Id="ID000">
</GlobalValue>
```

3.2.4.2 Real-world Sample

```
<GlobalValue Id="diameterSmall">10</GlobalValue>
```

3.2.5 MultiChoiceElement

| # | Name | Data Type | Description / Usage |
|----|----------------------------|------------------|--|
| 3. | Id | xsd:ID | DataElement identifier (can be referenced in other parts of module as well as by external systems) |
| 2 | CdeId (optional) | xsd:token | Common DataElement Id (intend to refer a standard definition in the ACR/RSNA CDE repository, radelement.org) |
| 3 | IsRequired | "true" "false" | Whether the DataElement is Required or not. |
| 4 | DisplaySequence (optional) | xsd:integer | Suggested order in which this DataElement is displayed together with the other DataElements |
| 5 | Label | text | Choice DataElement label (prompt text/display question for entering the value) |
| 6 | Hint (optional) | text | Optionally displayed more detailed text for the user describing how the DataElement needs to be filled in. |
| 7 | diagrams(optional) | | |

| | | | | | | |
|-------|---|------------------|---|--|--|--|
| | Contains one or more diagrams which offer additional information to the user (e.g.: illustrations of how the measurements are to be taken) | | | | | |
| 7.1 | diagram | | | | | |
| 7.1.1 | Location | text | Image location | | | |
| 7.1.2 | Label | text | Image Label | | | |
| 7.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | | | |
| 7.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram | | | |
| 8 | VoiceCommand (optional) | text | Voice command to find/activate the DataElement | | | |
| 9 | ChoiceInfo Contains all the possible values for the DataElement, only one value can be selected for a choice DataElement (for questions with multiple choice please use the MultiChoiceDataElement) | | | | | |
| 9.1 | Choice | | | | | |
| 9.1.1 | Value | xsd:token | Choice value | | | |
| 9.1.2 | Label | text | Choice label (how the choice is intended to be displayed for the user in the GUI) | | | |
| 9.1.3 | Hint (optional) | text | Further information on the choice which can be optional (e.g.: as a tooltip) | | | |
| 9.1.4 | VoiceCommand (optional) | text | Voice command to select this choice as the value for the DataElement | | | |
| 9.1.5 | Default | "true" "false" | Is this the default choice (if no other choice selected, this will be the value for the DataElement) | | | |
| 9.1.6 | ReportText (optional) | text | Text to be inserted into the report when the DataElement value is being inserted into the report. | | | |
| 10 | ImageMap (optional) Includes a pointer to the image that can be displayed as an interactive choice/multi choice question. Areas of the images which radiologist click should select one of the given choices. Image must be provided within the assets of the module. | | | | | |
| 10.1 | imageElements | xsd:anyURI | Image url pointing to the actual image location | | | |
| 10.2 | Label (optional) | text | Image Label, text used to referring the image. | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------|--------------------------------|--|---|--|--|--------------|---------------------------|-------------------------------|--|--|--------------|-----------------------------|------|---|--|--------------|--------------------------------|-----------|---|--|--------------|---------------------------|------|---|--|--------------|-----------------------------|------|--|--|--------------|--------------------------------|------|--|--|
| | 10.3 | <p>DrawStyle (optional) Draw style used in the image.</p> <table border="1"> <tr> <td>10.3. 1</td><td>Outline(optional)</td><td>text</td><td colspan="2">Default area outline color specified as hex code</td></tr> <tr> <td>10.3. 2</td><td>HoverFill(optional)</td><td>text</td><td colspan="2">Default area fill color when hovering specified as hex code</td></tr> <tr> <td>10.3. 3</td><td>SelectedFill(optional)</td><td>text</td><td colspan="2" rowspan="2">Default area fill color when selected specified as hex code</td></tr> </table> | | | | 10.3. 1 | Outline (optional) | text | Default area outline color specified as hex code | | 10.3. 2 | HoverFill (optional) | text | Default area fill color when hovering specified as hex code | | 10.3. 3 | SelectedFill (optional) | text | Default area fill color when selected specified as hex code | | | | | | | | | | | | | | | | |
| 10.3. 1 | Outline (optional) | text | Default area outline color specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.3. 2 | HoverFill (optional) | text | Default area fill color when hovering specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.3. 3 | SelectedFill (optional) | text | Default area fill color when selected specified as hex code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 10.4 | <p>Map</p> <p>10.4.1 Area Specifies region of the image to be which when selected activates a choice automatically. This has same concept as html image map, refer : http://www.w3schools.com/TAGS/tag_map.asp</p> <table border="1"> <tr> <td>10.4. 1.1</td><td>Shape</td><td>"rect" "poly" "circle"</td><td colspan="2">Supports three different shapes.</td></tr> <tr> <td>10.4. 1.2</td><td>Coords</td><td>text</td><td colspan="2">Image map coordinates</td></tr> <tr> <td>10.4. 1.3</td><td>ChoiceValue</td><td>xsd:token</td><td colspan="2">Choice value for this image map, which will activated when user clicks within the specified coordinates</td></tr> <tr> <td>10.4. 1.4</td><td>Outline(optional)</td><td>text</td><td colspan="2">Area outline color specified as hex code, which overrides the default defined in draw style</td></tr> <tr> <td>10.4. 1.5</td><td>HoverFill(optional)</td><td>text</td><td colspan="2">area fill color when hovering specified as hex code, which overrides the default defined in draw style</td></tr> <tr> <td>10.4. 1.6</td><td>SelectedFill(optional)</td><td>text</td><td colspan="2">area fill color when selected specified as hex code, which overrides the default defined in draw style</td></tr> </table> | | | | 10.4. 1.1 | Shape | "rect" "poly" "circle" | Supports three different shapes. | | 10.4. 1.2 | Coords | text | Image map coordinates | | 10.4. 1.3 | ChoiceValue | xsd:token | Choice value for this image map, which will activated when user clicks within the specified coordinates | | 10.4. 1.4 | Outline (optional) | text | Area outline color specified as hex code, which overrides the default defined in draw style | | 10.4. 1.5 | HoverFill (optional) | text | area fill color when hovering specified as hex code, which overrides the default defined in draw style | | 10.4. 1.6 | SelectedFill (optional) | text | area fill color when selected specified as hex code, which overrides the default defined in draw style | |
| 10.4. 1.1 | Shape | "rect" "poly" "circle" | Supports three different shapes. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.4. 1.2 | Coords | text | Image map coordinates | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.4. 1.3 | ChoiceValue | xsd:token | Choice value for this image map, which will activated when user clicks within the specified coordinates | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.4. 1.4 | Outline (optional) | text | Area outline color specified as hex code, which overrides the default defined in draw style | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.4. 1.5 | HoverFill (optional) | text | area fill color when hovering specified as hex code, which overrides the default defined in draw style | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.4. 1.6 | SelectedFill (optional) | text | area fill color when selected specified as hex code, which overrides the default defined in draw style | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

3.2.5.1 Sample

```

<MultiChoiceDataElement Id="ID000" CdId="CdId0"
    IsRequired="true" DisplaySequence="50">
    <Label>Label0</Label>
    <Hint>Hint0</Hint>
    <Diagrams>
        <Diagram DisplaySequence="0" KeyDiagram="true">
            <Location>Location0</Location>
            <Label>Label1</Label>
        </Diagram>
        <Diagram DisplaySequence="0" KeyDiagram="true">
            <Location>Location1</Location>
            <Label>Label2</Label>
        </Diagram>
    </Diagrams>
    <VoiceCommand>VoiceCommand0</VoiceCommand>
    <ChoiceInfo>
        <Choice Default="true">
            <Value>Value0</Value>
            <Label>Label3</Label>
            <Hint>Hint1</Hint>
            <VoiceCommand>VoiceCommand1</VoiceCommand>
            <ReportText>ReportText0</ReportText>
        </Choice>
        <Choice Default="true">
            <Value>Value1</Value>
            <Label>Label4</Label>
            <Hint>Hint2</Hint>
            <VoiceCommand>VoiceCommand2</VoiceCommand>
            <ReportText>ReportText1</ReportText>
        </Choice>
        <Choice Default="true">
            <Value>Value2</Value>
            <Label>Label5</Label>
            <Hint>Hint3</Hint>
            <VoiceCommand>VoiceCommand3</VoiceCommand>
            <ReportText>ReportText2</ReportText>
        </Choice>
    </ChoiceInfo>
    <ImageMap>
        <imageElements>http://www.url.com/</imageElements>
        <Label>Label6</Label>
        <DrawStyle Outline="Outline0" HoverFill="HoverFill0" SelectedFill="SelectedFill0"/>
        <Map>
            <Area Shape="rect" Coords="Coords0" ChoiceValue="ChoiceValue0" Outline="Outline1"
                HoverFill="HoverFill1" SelectedFill="SelectedFill1"/>
            <Area Shape="rect" Coords="Coords1" ChoiceValue="ChoiceValue1" Outline="Outline2"
                HoverFill="HoverFill2" SelectedFill="SelectedFill2"/>
        </Map>
    </ImageMap>

```

```
</MultiChoiceDataElement>
```

3.2.5.2 Real-world Sample

```
<MultiChoiceDataElement Id="ancillaryFavoringMalignancy" DisplaySequence="7">
    <Label>Are there Ancillary features favoring malignancy? </Label>
    <Hint>Imaging features that modify likelihood of HCC. In isolation, these features do not permit reliable categorization of observations and hence are considered ancillary.</Hint>
    <Diagrams>
        <Diagram>
            <Location>AF_favoringMal1.png</Location>
            <Label></Label>
        </Diagram>
        <Diagram>
            <Location>AF_favoringMal2.png</Location>
            <Label></Label>
        </Diagram>
        <Diagram>
            <Location>AF_favoringMal3.png</Location>
            <Label></Label>
        </Diagram>
    </Diagrams>
    <ChoiceInfo>
        <Choice>
            <Value>Hepatobiliaryphasehypointensity</Value>
            <Label>Hepatobiliary phase hypointensity</Label>
            <Hint>Intensity in the hepatobiliary phase that unequivocally is less than that of the surrounding liver</Hint>
            <ReportText>Hepatobiliary phase hypointensity</ReportText>
        </Choice>
        <Choice>
            <Value>Transitionalphasehypointensity</Value>
            <Label>Transitional phase hypointensity</Label>
            <Hint>Intensity in the transitional phase that unequivocally is less than that of the surrounding liver</Hint>
            <ReportText>Transitional phase hypointensity</ReportText>
        </Choice>
        <Choice>
            <Value>Mild-moderateT2hyperintensity</Value>
            <Label>Mild-moderate T2 hyperintensity</Label>
            <Hint>Having mildly or moderately higher signal intensity on T2w images than liver.</Hint>
            <ReportText>Mild-moderate T2 hyperintensity</ReportText>
        </Choice>
        <Choice>
            <Value>Restricteddiffusion</Value>
            <Label>Restricted diffusion</Label>
            <ReportText>Restricted diffusion</ReportText>
        </Choice>
        <Choice>

```

```

<Value>Distinctiverim</Value>
<Label>Distinctive rim</Label>
<Hint>Features that specifically favor HCC as opposed to malignancy in general</Hint>
<ReportText>Distinctive rim</ReportText>
</Choice>
<Choice>
    <Value>Coronaenhancement</Value>
    <Label>Coronaenhancement</Label>
    <Hint>Zone or rim of peri-observation enhancement in the late arterial phase or early
portal venous phase occurring after rapid dissipation of contrast material from an arterial phase hyperenhancing
mass.</Hint>
        <ReportText>Coronaenhancement</ReportText>
    </Choice>
    <Choice>
        <Value>Mosaicarchitecture</Value>
        <Label>Mosaic architecture</Label>
        <Hint>Observation that appears to consist of nodules or compartments with differing
appearances (enhancement, attenuation, intensity). This term can also be applied to lesions with internal enhancing
septations. The nodules, compartments, or septations appear randomly distributed within the observation.</Hint>
            <ReportText>Mosaic architecture</ReportText>
        </Choice>
        <Choice>
            <Value>Nodule-in-nodularchitecture</Value>
            <Label>Nodule-in-nodularchitecture</Label>
            <Hint>One or more nodular or nodule-like observations within a larger nodular or
nodular-like observation.</Hint>
                <ReportText>Nodule-in-nodularchitecture</ReportText>
            </Choice>
            <Choice>
                <Value>Intra-lesionalfat</Value>
                <Label>Intra-lesional fat</Label>
                <Hint>Presence of lipid in higher concentration within a mass than in background
reference tissue (e.g. liver).</Hint>
                    <ReportText>Intra-lesional fat</ReportText>
                </Choice>
                <Choice>
                    <Value>Lesionalironsparing</Value>
                    <Label>Lesional iron sparing</Label>
                    <Hint>Relative paucity of iron in a solid mass compared to that of background reference
tissue (e.g. iron-overloaded liver).</Hint>
                        <ReportText>Lesional iron sparing</ReportText>
                    </Choice>
                    <Choice>
                        <Value>Lesionalfatsparing</Value>
                        <Label>Lesional fat sparing</Label>
                        <Hint>Relative paucity of fat in solid mass compared to that of background reference
tissue (e.g. fatty liver).</Hint>
                            <ReportText>Lesional fat sparing</ReportText>
                        </Choice>
                        <Choice>
                            <Value>Bloodproducts</Value>

```

```

<Label>Blood products</Label>
<Hint>Presence of intra-lesional or peri-lesional hemorrhage in absence of biopsy, trauma
or intervention.</Hint>
<ReportText>Blood products</ReportText>
</Choice>
<Choice>
<Value>Diameter increase less than threshold growth</Value>
<Label>Diameter increase less than threshold growth</Label>
<Hint>Unequivocal increase in the diameter of an observation, measured on
examinations performed on different dates, which is not attributable to artifact, differences in technique between the two
examinations, or measurement error.</Hint>
<ReportText>Diameter increase less than threshold growth</ReportText>
</Choice>
</ChoiceInfo>
</MultiChoiceDataElement>

```

3.2.6 ComputedElement

| # | Name | Data Type | Description / Usage | | | | | | | | | | | | | | | | | | | | |
|-------|--|------------------|--|-----|----------------|--|--|-------|-----------------|------|----------------|-------|--------------|------|-------------|-------|-----------------------------------|-------------|--|-------|------------------------------|------------------|---------------------------------|
| 1 | Id | xsd:ID | DataElement identifier (can be referenced in other parts of module as well as by external systems) | | | | | | | | | | | | | | | | | | | | |
| 2 | DisplaySequence (optional) | xsd:integer | Suggested order in which this DataElement is displayed together with the other DataElements | | | | | | | | | | | | | | | | | | | | |
| 3 | ShowValue (optional) | xsd:boolean | If true, then the computed value of the ComputedElement should be displayed in the interface of the reporting framework. | | | | | | | | | | | | | | | | | | | | |
| 4 | Label (optional) | Text | Computed DataElement label | | | | | | | | | | | | | | | | | | | | |
| 5 | Hint (optional) | text | Optionally displayed more detailed text for the user describing more details about the DataElement. | | | | | | | | | | | | | | | | | | | | |
| 6 | Diagrams (optional) Contains one or more diagrams which offer additional information to the user (e.g.: illustrations of how the measurements are to be taken | | <table border="1"> <tr> <td>6.1</td> <td>diagram</td> <td></td> <td></td> </tr> <tr> <td>6.1.1</td> <td>Location</td> <td>text</td> <td>Image location</td> </tr> <tr> <td>6.1.2</td> <td>Label</td> <td>text</td> <td>Image Label</td> </tr> <tr> <td>6.1.3</td> <td>DisplaySequence(optional)</td> <td>xsd:integer</td> <td>Image display sequence if the DataElement contains more than one diagram</td> </tr> <tr> <td>6.1.4</td> <td>KeyDiagram(optional)</td> <td>"true" "false"</td> <td>Whether this is the key diagram</td> </tr> </table> | 6.1 | diagram | | | 6.1.1 | Location | text | Image location | 6.1.2 | Label | text | Image Label | 6.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | 6.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram |
| 6.1 | diagram | | | | | | | | | | | | | | | | | | | | | | |
| 6.1.1 | Location | text | Image location | | | | | | | | | | | | | | | | | | | | |
| 6.1.2 | Label | text | Image Label | | | | | | | | | | | | | | | | | | | | |
| 6.1.3 | DisplaySequence (optional) | xsd:integer | Image display sequence if the DataElement contains more than one diagram | | | | | | | | | | | | | | | | | | | | |
| 6.1.4 | KeyDiagram (optional) | "true" "false" | Whether this is the key diagram | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | |
|-------|---|--|---|--|-----------|--|---|-------------------------------------|--------------------|---|-------|---------------------|---|-------|---|--|
| | | | | | | | | | | | | | | | | |
| 7 | ArithmeticExpression | text Arithmetic expression which will be evaluated to produce the output. This can include values from other DataElement, basic arithmetic operators, many core mathematical functions | | | | | | | | | | | | | | |
| 8 | TextExpression Text expression is the desired computed output value of the computed DataElement, which can include reference to other DataElements. | | | | | | | | | | | | | | | |
| 8.1 | text | Text Expression. | | | | | | | | | | | | | | |
| 8.2 | InsertValue Can be used to insert the value of a Dataelement | <table border="1"> <tr> <td>8.2.1</td><td>DataElementId</td><td>xsd:IDREF</td><td>The value of this Dataelement will be inserted</td></tr> <tr> <td>8.2.2</td><td>SignificantDigits(optional)</td><td>xsd:integer</td><td>This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text.</td></tr> </table> | 8.2.1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | 8.2.2 | SignificantDigits (optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | | | | | | |
| 8.2.1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | | | | | | | | | | | | | |
| 8.2.2 | SignificantDigits (optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | | | | | | | | | | | | | |
| 9 | DecisionPoint Text expression can be written as simple text expression, which will be returned as the value of the computed element. It is also possible to insert any Dataelement value in the expression. Contains different Braches each meets a unique condition. | <table border="1"> <tr> <td>9.1</td><td>Branch ConditionType Below are the possible conditions in a branch. Condition type enable comparing DataElements to one another to fixed values, operators allows combination of conditions itself</td></tr> <tr> <td>9.1.1</td><td>AndCondition</td><td>It contains conditions if all of those evaluate to true then it evaluates to true</td></tr> <tr> <td>9.1.2</td><td>OrCondition</td><td>It contains conditions if any of those evaluate to true then it evaluates to true</td></tr> <tr> <td>9.1.3</td><td>NotCondition</td><td>It contains conditions if all of those evaluate to false then it evaluates to true.</td></tr> <tr> <td>9.1.4</td><td>EqualCondition Compare a DataElement to a given value and evaluated to “true” if they are equal</td><td></td></tr> </table> | 9.1 | Branch ConditionType Below are the possible conditions in a branch. Condition type enable comparing DataElements to one another to fixed values, operators allows combination of conditions itself | 9.1.1 | AndCondition | It contains conditions if all of those evaluate to true then it evaluates to true | 9.1.2 | OrCondition | It contains conditions if any of those evaluate to true then it evaluates to true | 9.1.3 | NotCondition | It contains conditions if all of those evaluate to false then it evaluates to true. | 9.1.4 | EqualCondition Compare a DataElement to a given value and evaluated to “true” if they are equal | |
| 9.1 | Branch ConditionType Below are the possible conditions in a branch. Condition type enable comparing DataElements to one another to fixed values, operators allows combination of conditions itself | | | | | | | | | | | | | | | |
| 9.1.1 | AndCondition | It contains conditions if all of those evaluate to true then it evaluates to true | | | | | | | | | | | | | | |
| 9.1.2 | OrCondition | It contains conditions if any of those evaluate to true then it evaluates to true | | | | | | | | | | | | | | |
| 9.1.3 | NotCondition | It contains conditions if all of those evaluate to false then it evaluates to true. | | | | | | | | | | | | | | |
| 9.1.4 | EqualCondition Compare a DataElement to a given value and evaluated to “true” if they are equal | | | | | | | | | | | | | | | |

| | | | |
|-------|--|---------------------------------|--|
| | | | comparisonConditionContents |
| | 9.1.4. | dataElementIdAttribute | |
| | 1 | DataElement used for comparison | |
| | 9.1. | | |
| | 4.1. | DataEle mentId | xsd:IDREF |
| | 1 | | DataElementId to be compared |
| | 9.1.4. | ComparisonValu e | xsd:token |
| | 2 | | Comparison value. Could be an id of a DataElement or a constant value. |
| 9.1.5 | GreaterThanCondition Checks whether DataElement value is greater than given value and evaluated to “true” if so. | | |
| | 9.1. | dataElementIdAttribute | |
| | 5.1 | DataElement used for comparison | |
| | 9.1. | | |
| | 5.1. | DataEle mentId | xsd:IDREF |
| | 1 | | DataElementId to be compared |
| | 9.1. | ComparisonValu e | xsd:token |
| | 5.2 | | Comparison value. Could be an id of a DataElement or a constant value. |
| 9.1.6 | LessThanCondition Checks whether DataElement value is lesser than given value and evaluated to “true” if so | | |
| | 9.1. | dataElementIdAttribute | |
| | 6.1 | DataElement used for comparison | |
| | 9.1. | | |
| | 6.1. | DataEle mentId | xsd:IDREF |
| | 1 | | DataElementId to be compared |
| | 9.1. | ComparisonValu e | xsd:token |
| | 6.2 | | Comparison value. Could be an id of a DataElement or a constant value. |
| 9.1.7 | GreaterThanOrEqualsCondition Checks whether DataElement value is greater than or equal to given value and | | |

| | | | | | | |
|--------|---|-------|---|--|--|--|
| | | | evaluated to “true” if so | | | |
| | 9.1. | 9.1.1 | dataElementIdAttribute DataElement used for comparison | | | |
| | 7.1 | 7.1.1 | xsd:IDREF DataElementId to be compared | | | |
| | 9.1. | 9.1.2 | ComparisonValue xsd:token Comparison value. Could be an id of a DataElement or a constant value. | | | |
| 9.1.8 | LessThanOrEqualsCondition Checks whether DataElement value is lesser than or equal to given value and evaluated to “true” if so | | | | | |
| | 9.1. | 9.1.1 | dataElementIdAttribute DataElement used for comparison | | | |
| | 8.1 | 8.1.1 | xsd:IDREF DataElementId to be compared | | | |
| | 9.1. | 9.1.2 | ComparisonValue xsd:token Comparison value. Could be an id of a DataElement or a constant value. | | | |
| 9.1.9 | ContainsCondition Checks whether any part of the DataElement matches with the given value and evaluated to “true” if so | | | | | |
| | 9.1. | 9.1.1 | dataElementIdAttribute DataElement used to check contains condition | | | |
| | 9.1. | 9.1.1 | xsd:IDREF DataElementId to be checked | | | |
| | 9.1. | 9.1.2 | ComparisonValue xsd:token Comparison value. Could be a constant value. | | | |
| 9.1.10 | HasAnyNChoicesCondition This can be used to compare the number of choices selected from a MultiChoice | | | | | |

| | | | |
|-----|--|---|---|
| | | | DataElement and evaluated to “true” if so |
| | 9.1. 10.1 | dataElementIdAttribute DataElement used to check contains condition | |
| | 9.1.1 0.1.1 | DataEle mentId | xsd:IDREF MultiChoice DataElementId to be checked |
| | 9.1. 10.2 | MinimumChoice s | xsd:positiveInt eger Constant value which can be compared with the number of choices selected. |
| 9.2 | Recursive. Can be ArithmeticExpression , TextExpression or DecisionPoint | | |
| 10 | DefaultBranch Recursive. Can be ArithmeticExpression , TextExpression or DecisionPoint | | |

3.2.6.1 Sample:

```
<ComputedElement Id="ID000" DisplaySequence="50" ShowValue="false">
  <Label>Label0</Label>
  <Hint>Hint0</Hint>
  <Diagrams>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location0</Location>
      <Label>Label1</Label>
    </Diagram>
    <Diagram DisplaySequence="0" KeyDiagram="true">
      <Location>Location1</Location>
      <Label>Label2</Label>
    </Diagram>
  </Diagrams>
  <DecisionPoint>
    <Branch>
      <AndCondition>
        <LessThanCondition DataElementId="ID000" ComparisonValue="ComparisonValue0"/>
        <NotCondition>
          </NotCondition>
        <GreaterThanCondition DataElementId="ID000" ComparisonValue="ComparisonValue1"/>
      </AndCondition>
      <DecisionPoint/>
    </Branch>
    <Branch>
      <LessThanCondition DataElementId="ID000" ComparisonValue="ComparisonValue2"/>
      <DecisionPoint/>
    </Branch>
  <DefaultBranch>
```

```

<ArithmeticExpression>ArithmeticExpression0</ArithmeticExpression>
</DefaultBranch>
</DecisionPoint>
</ComputedElement>

```

3.2.6.2 Real-world Sample

```

<ComputedElement Id="washoutcapsulethreshold">
  <DecisionPoint>
    <Branch>
      <AndCondition>
        <EqualCondition DataElementId="washout" ComparisonValue="no"/>
        <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
        <EqualCondition DataElementId="thresholdgrowth" ComparisonValue="no"/>
      </AndCondition>
      <TextExpression>None</TextExpression>
    </Branch>
    <Branch>
      <OrCondition>
        <AndCondition>
          <EqualCondition DataElementId="washout" ComparisonValue="yes"/>
          <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
          <EqualCondition DataElementId="thresholdgrowth" ComparisonValue="no"/>
        </AndCondition>
        <AndCondition>
          <EqualCondition DataElementId="washout" ComparisonValue="no"/>
          <EqualCondition DataElementId="capsule" ComparisonValue="yes"/>
          <EqualCondition DataElementId="thresholdgrowth" ComparisonValue="no"/>
        </AndCondition>
        <AndCondition>
          <EqualCondition DataElementId="washout" ComparisonValue="no"/>
          <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
          <EqualCondition DataElementId="thresholdgrowth" ComparisonValue="yes"/>
        </AndCondition>
      </OrCondition>
      <TextExpression>One</TextExpression>
    </Branch>
    <DefaultBranch>
      <TextExpression>twoormore</TextExpression>
    </DefaultBranch>
  </DecisionPoint>
</ComputedElement>

<ComputedElement Id="famHxLungCancerFactor">
  <DecisionPoint>
    <Branch>
      <EqualCondition DataElementId="famHxLungCancer" ComparisonValue="true"/>
    </Branch>

```

```

<ArithmeticExpression>0.2961</ArithmeticExpression>
</Branch>
<DefaultBranch>
  <ArithmeticExpression>0</ArithmeticExpression>
</DefaultBranch>
</DecisionPoint>
</ComputedElement>

```

3.3 Rules

The Rules section consists of a root DecisionPoint element containing multiple Branch elements, each of which consists of a condition which if true leads to a DecisionPoint element or to an EndPointRef element.

| # | Name | Data Type | Description / Usage | | | | |
|---------|---|-----------|---|---------|-------------------------------|-----------|---|
| 1 | Id | xsd:ID | Identifier | | | | |
| 2 | Label | text | Decision point label. | | | | |
| 3 | Description(optional) | text | Decision point description | | | | |
| 4 | Branch A branch either ends on an endpoint or on a decision point. The decision point can contain one more branches based on different conditions. | | | | | | |
| 4.1 | Label(optional) | text | | | | | |
| 4.2 | NotRelevantDataElements(optional) This property can be used to specify the list the DataElements which are not relevant down this branch. It is suggested that NotRelevantDataElements been either deactivated or hide on this branch. | | | | | | |
| 4.2.1 | DataElementRef <table border="1"> <tr> <td>4.2.1.1</td><td>DataElementId</td><td>xsd:IDREF</td><td>Dataelement identifier which is no relevant</td></tr> </table> | | | 4.2.1.1 | DataElementId | xsd:IDREF | Dataelement identifier which is no relevant |
| 4.2.1.1 | DataElementId | xsd:IDREF | Dataelement identifier which is no relevant | | | | |
| 4.3 | AndCondition | | It contains conditions if all of those evaluate to true then it evaluates to true | | | | |
| 4.4 | OrCondition | | It contains conditions if any of those evaluate to true then it evaluates to true | | | | |
| 4.5 | NotCondition | | It contains conditions if all of those evaluate to false then it evaluates to true. | | | | |
| 4.6 | EqualCondition Compare a DataElement to a given value and evaluated to "true" if they are equal | | | | | | |

| | | | | | | | | | | | | | |
|-------------|--|-----------|--|-----------|--|-------------|---------------|-----------|-------------------------------|-------------|-----------------|-----------|--|
| | | 4.6. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | |
| | | 4.6. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | |
| 4.7 | GreaterThanCondition Checks whether DataElement value is greater than given value and evaluated to “true” if so. | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>4.7. 1</td><td>DataElementId</td><td>xsd:IDREF</td><td>DataElementId to be compared.</td></tr> <tr> <td>4.7. 2</td><td>ComparisonValue</td><td>xsd:token</td><td>Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | | 4.7. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | 4.7. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. |
| 4.7. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | |
| 4.7. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | |
| 4.8 | LessThanCondition Checks whether DataElement value is lesser than given value and evaluated to “true” if so | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>4.8. 1</td><td>DataElementId</td><td>xsd:IDREF</td><td>DataElementId to be compared.</td></tr> <tr> <td>4.8. 2</td><td>ComparisonValue</td><td>xsd:token</td><td>Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | | 4.8. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | 4.8. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. |
| 4.8. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | |
| 4.8. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | |
| 4.9 | GreaterThanOrEqualsCondition Checks whether DataElement value is greater than or equal to given value and evaluated to “true” if so | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>4.9. 1</td><td>DataElementId</td><td>xsd:IDREF</td><td>DataElementId to be compared.</td></tr> <tr> <td>4.9. 2</td><td>ComparisonValue</td><td>xsd:token</td><td>Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | | 4.9. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | 4.9. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. |
| 4.9. 1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | |
| 4.9. 2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | |
| 4.10 | LessThanOrEqualsCondition Checks whether DataElement value is lesser than or equal to given value and evaluated to “true” if so | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>4.10. .1</td><td>DataElementId</td><td>xsd:IDREF</td><td>DataElementId to be compared.</td></tr> <tr> <td>4.10. .2</td><td>ComparisonValue</td><td>xsd:token</td><td>Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | | 4.10. .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | 4.10. .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. |
| 4.10. .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | |
| 4.10. .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | |
| 4.11 | ContainsCondition Checks whether any part of the DataElement matches with the given value and evaluated to | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------|---|---|--|-------------------------------------|--|------------|-------------------------|-----------|--|--|--|------------|---|----------------------|--|-------------------------------------|--|------------|-------------------------------|------|--------------------------------|--|--|--|------|----------------------|-----------|-------------------------------------|--|
| | | <p>“true” if so</p> <table border="1"> <tr> <td>4.11 .1</td><td>DataElementId</td><td>xsd:IDREF</td><td colspan="3">DataElementId to be compared.</td></tr> <tr> <td>4.11 .2</td><td>ComparisonValue</td><td>xsd:token</td><td colspan="3" rowspan="2">Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | 4.11 .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | 4.11 .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | | | | | |
| 4.11 .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.11 .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 4.12 | <p>HasAnyNChoicesCondition This can be used to compare the number of choices selected from a MultiChoice DataElement and evaluated to “true” if so</p> <table border="1"> <tr> <td>4.12 .1</td><td>DataElementId</td><td>xsd:IDREF</td><td colspan="3">DataElementId to be compared.</td></tr> <tr> <td>4.12 .2</td><td>ComparisonValue</td><td>xsd:token</td><td colspan="3" rowspan="2">Comparison value. Could be an id of a DataElement or a constant value.</td></tr> </table> | | | | 4.12 .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | 4.12 .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | | | | | |
| 4.12 .1 | DataElementId | xsd:IDREF | DataElementId to be compared. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.12 .2 | ComparisonValue | xsd:token | Comparison value. Could be an id of a DataElement or a constant value. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 4.13 | <p>EndpointRef Reference to the endpoint which is the output of the rule set.</p> <table border="1"> <tr> <td>4.13.1</td><td>EndPointId</td><td>xsd:IDREF</td><td colspan="3">The endpoint id reference.</td></tr> <tr> <td>4.13.2</td><td>Label(optional)</td><td>text</td><td colspan="3">Endpoint reference label, which can be used in reference documentation and/or graphical representations.</td></tr> <tr> <td>4.13.3</td><td>Description(optional)</td><td>text</td><td colspan="3" rowspan="3">Endpoint reference description</td></tr> </table> | | | | 4.13.1 | EndPointId | xsd:IDREF | The endpoint id reference. | | | 4.13.2 | Label (optional) | text | Endpoint reference label, which can be used in reference documentation and/or graphical representations. | | | 4.13.3 | Description (optional) | text | Endpoint reference description | | | | | | | | |
| 4.13.1 | EndPointId | xsd:IDREF | The endpoint id reference. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.13.2 | Label (optional) | text | Endpoint reference label, which can be used in reference documentation and/or graphical representations. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.13.3 | Description (optional) | text | Endpoint reference description | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 4.14 | <p>DecisionPoint Recursive, starts another DecisionPoint</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | <p>DefaultBranch(optional) Default branch if no other branch in the decision point that evaluates to true</p> <table border="1"> <tr> <td>5.1</td><td>Label(optional)</td><td>text</td><td colspan="3" rowspan="2">Default branch label, which can be used in reference documentation and/or graphical representations.</td></tr> <tr> <td>5.2</td><td colspan="5"> <p>NotRelevantDataElements(optional) This property can be used to specify the list the DataElements which are not relevant down this branch. It is suggested that nonrelevantDataElements been either deactivated or hide on this branch.</p> <table border="1"> <tr> <td>5.2 .1.</td><td>DataElementRef</td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td>5.2.</td><td>DataElementId</td><td>xsd:IDREF</td><td colspan="2">DataElementId which is not relevant</td></tr> </table> </td></tr> </table> | | | | | 5.1 | Label (optional) | text | Default branch label, which can be used in reference documentation and/or graphical representations. | | | 5.2 | <p>NotRelevantDataElements(optional) This property can be used to specify the list the DataElements which are not relevant down this branch. It is suggested that nonrelevantDataElements been either deactivated or hide on this branch.</p> <table border="1"> <tr> <td>5.2 .1.</td><td>DataElementRef</td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td>5.2.</td><td>DataElementId</td><td>xsd:IDREF</td><td colspan="2">DataElementId which is not relevant</td></tr> </table> | | | | | 5.2 .1. | DataElementRef | | | | | | 5.2. | DataElementId | xsd:IDREF | DataElementId which is not relevant | |
| 5.1 | Label (optional) | text | Default branch label, which can be used in reference documentation and/or graphical representations. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.2 | <p>NotRelevantDataElements(optional) This property can be used to specify the list the DataElements which are not relevant down this branch. It is suggested that nonrelevantDataElements been either deactivated or hide on this branch.</p> <table border="1"> <tr> <td>5.2 .1.</td><td>DataElementRef</td><td></td><td></td><td></td><td></td></tr> <tr> <td></td><td>5.2.</td><td>DataElementId</td><td>xsd:IDREF</td><td colspan="2">DataElementId which is not relevant</td></tr> </table> | | | | | 5.2 .1. | DataElementRef | | | | | | 5.2. | DataElementId | xsd:IDREF | DataElementId which is not relevant | | | | | | | | | | | | | |
| 5.2 .1. | DataElementRef | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 5.2. | DataElementId | xsd:IDREF | DataElementId which is not relevant | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | |
|-----|---|-------------------------------|-----------|---|--|
| | | | 1.1 | | |
| | 5.3 EndpointRef Reference to the endpoint which is the output of the rule set | | | | |
| | 5.3.1 | EndPointId | xsd:IDREF | The endpoint id reference. | |
| | 5.3.2 | Label (optional) | text | Endpoint reference label, which can be used in reference documentation and/or graphical representations | |
| | 5.3.3 | Description (optional) | text | Endpoint reference description | |
| 5.4 | DecisionPoint Recursive, starts another DecisionPoint | | | | |

3.3.1 Sample

```

<Rules>
  <DecisionPoint>
    <Label>Label0</Label>
    <Description>Description0</Description>
    <Branch>
      <Label>Label1</Label>
      <NotRelevantDataElements>
        <DataElementRef DataElementId="ID000"/>
        <DataElementRef DataElementId="ID001"/>
      </NotRelevantDataElements>
      <EqualCondition DataElementId="ID002" ComparisonValue="ComparisonValue0"/>
      <DecisionPoint/>
    </Branch>
    <Branch>
      <Label>Label2</Label>
      <NotRelevantDataElements>
        <DataElementRef DataElementId="ID003"/>
        <DataElementRef DataElementId="ID004"/>
      </NotRelevantDataElements>
      <OrCondition>
        <AndCondition></AndCondition>
        <GreaterThanOrEqualsCondition DataElementId="ID005"
          ComparisonValue="ComparisonValue1"/>
        <ContainsCondition DataElementId="ID006" ComparisonValue="ComparisonValue2"/>
      </OrCondition>
      <DecisionPoint/>
    </Branch>
    <DefaultBranch>
  
```


```

<Label>Label3</Label>
<NotRelevantDataElements>
  <DataElementRef DataElementId="ID007"/>
  <DataElementRef DataElementId="ID008"/>
</NotRelevantDataElements>
<DecisionPoint/>
</DefaultBranch>
</DecisionPoint>
</Rules>

```

3.3.2 Real-world Sample

Hello_RADs diagram and its Rules section representation.



```

<Rules>
  <DecisionPoint>
    <Label>Observation character</Label>
    <Branch>
      <Label>Treated Observation</Label>
      <NotRelevantDataElements>
        <DataElementRef DataElementId="diameter"/>
        <DataElementRef DataElementId="arterialEnhancement"/>
      </NotRelevantDataElements>
    </Branch>
  </DecisionPoint>
</Rules>

```

```

<DataElementRef DataElementId="washout"/>
<DataElementRef DataElementId="capsule"/>
<DataElementRef DataElementId="thresholdgrowth"/>
<DataElementRef DataElementId="ancillaryFavoringMalignancy"/>
<DataElementRef DataElementId="ancillaryFavoringBenignity"/>
<DataElementRef DataElementId="adjustcategorybasedonAncillary"/>
</NotRelevantDataElements>
<EqualCondition DataElementId="observationCharacter"
    ComparisonValue="treatedObservation"/>
<EndPointRef EndPointId="hcctreatedEp"/>
</Branch>
<Branch>
    <Label>Definitely Benign</Label>
    <NotRelevantDataElements>
        <DataElementRef DataElementId="diameter"/>
        <DataElementRef DataElementId="arterialEnhancement"/>
        <DataElementRef DataElementId="washout"/>
        <DataElementRef DataElementId="capsule"/>
        <DataElementRef DataElementId="thresholdgrowth"/>
        <DataElementRef DataElementId="ancillaryFavoringMalignancy"/>
        <DataElementRef DataElementId="ancillaryFavoringBenignity"/>
        <DataElementRef DataElementId="adjustcategorybasedonAncillary"/>
    </NotRelevantDataElements>
    <EqualCondition DataElementId="observationCharacter" ComparisonValue="definitelyBenign"/>
    <EndPointRef EndPointId="hcc1Ep"/>
</Branch>
<Branch>
    <Label>Probably Benign</Label>
    <NotRelevantDataElements>
        <DataElementRef DataElementId="diameter"/>
        <DataElementRef DataElementId="arterialEnhancement"/>
        <DataElementRef DataElementId="washout"/>
        <DataElementRef DataElementId="capsule"/>
        <DataElementRef DataElementId="thresholdgrowth"/>
        <DataElementRef DataElementId="ancillaryFavoringMalignancy"/>
        <DataElementRef DataElementId="ancillaryFavoringBenignity"/>
        <DataElementRef DataElementId="adjustcategorybasedonAncillary"/>
    </NotRelevantDataElements>
    <EqualCondition DataElementId="observationCharacter" ComparisonValue="probablyBenign"/>
    <EndPointRef EndPointId="hcc2Ep"/>
</Branch>
<Branch>
    <Label>Probable malignancy, not specific for HCC</Label>
    <NotRelevantDataElements>
        <DataElementRef DataElementId="diameter"/>
        <DataElementRef DataElementId="arterialEnhancement"/>
        <DataElementRef DataElementId="washout"/>
        <DataElementRef DataElementId="capsule"/>
        <DataElementRef DataElementId="thresholdgrowth"/>
        <DataElementRef DataElementId="ancillaryFavoringMalignancy"/>
        <DataElementRef DataElementId="ancillaryFavoringBenignity"/>
    </NotRelevantDataElements>

```

```

<DataElementRef DataElementId="adjustcategorybasedonAncillary"/>
</NotRelevantDataElements>
<EqualCondition DataElementId="observationCharacter" ComparisonValue="notspecificforhcc"/>
<EndPointRef EndPointId="hccmEp"/>
</Branch>
<Branch>
  <Label>Tumor in vein</Label>
  <NotRelevantDataElements>
    <DataElementRef DataElementId="diameter"/>
    <DataElementRef DataElementId="arterialEnhancement"/>
    <DataElementRef DataElementId="washout"/>
    <DataElementRef DataElementId="capsule"/>
    <DataElementRef DataElementId="thresholdgrowth"/>
    <DataElementRef DataElementId="ancillaryFavoringMalignancy"/>
    <DataElementRef DataElementId="ancillaryFavoringBenignity"/>
    <DataElementRef DataElementId="adjustcategorybasedonAncillary"/>
  </NotRelevantDataElements>
  <EqualCondition DataElementId="observationCharacter" ComparisonValue="tumorInVein"/>
  <EndPointRef EndPointId="hcc5vEp"/>
</Branch>
<Branch>
  <Label>Neither definite nor probable benign</Label>
  <AndCondition>
    <EqualCondition DataElementId="observationCharacter"
      ComparisonValue="notDefProbBenign"/>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary" ComparisonValue="No"
      />
  </AndCondition>
  <DecisionPoint>
    <Label>Arterial phase enhancement</Label>
    <Branch>
      <Label>Hyper-enhancement</Label>
      <!-- Hyper-enhancement -->
      <EqualCondition DataElementId="arterialEnhancement"
        ComparisonValue="hyperEnhancing"/>
    <DecisionPoint>
      <Label>Diameter</Label>
      <Branch>
        <Label>&lt; 10</Label>
        <!-- Diameter < 10 -->
        <LessThanCondition DataElementId="diameter"
          ComparisonValue="diameterSmall"/>
      <DecisionPoint>
        <Label>Washout/Capsule/Thresholdgrowth</Label>
        <Branch>
          <Label>None</Label>
          <!-- None / Zero Y's -->
          <AndCondition>
            <EqualCondition DataElementId="washout" ComparisonValue="no"/>
            <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
            <EqualCondition DataElementId="thresholdgrowth"/>

```

```

        ComparisonValue="no"/>
    </AndCondition>
    <EndPointRef EndPointId="hcc3Ep"/>
</Branch>
<Branch>
    <Label>One</Label>
    <!-- One / One Y -->
    <OrCondition>
        <AndCondition>
            <EqualCondition DataElementId="washout"
                ComparisonValue="yes"/>
            <!-- Washout = Yes -->
            <EqualCondition DataElementId="capsule"
                ComparisonValue="no"/>
            <EqualCondition DataElementId="thresholdgrowth"
                ComparisonValue="no"/>
        </AndCondition>
        <AndCondition>
            <EqualCondition DataElementId="washout"
                ComparisonValue="no"/>
            <!-- Capsule = Yes -->
            <EqualCondition DataElementId="capsule"
                ComparisonValue="yes"/>
            <EqualCondition DataElementId="thresholdgrowth"
                ComparisonValue="no"/>
        </AndCondition>
        <AndCondition>
            <EqualCondition DataElementId="washout"
                ComparisonValue="no"/>
            <!-- Thresholdgrowth = Yes -->
            <EqualCondition DataElementId="capsule"
                ComparisonValue="no"/>
            <EqualCondition DataElementId="thresholdgrowth"
                ComparisonValue="yes"/>
        </AndCondition>
    </OrCondition>
    <EndPointRef EndPointId="hcc4Ep"/>
</Branch>
<Branch>
    <Label>Two or More</Label>
    <!-- Two / Two or more Y's -->
    <OrCondition>
        <AndCondition>
            <EqualCondition DataElementId="washout"
                ComparisonValue="yes"/>
            <!-- Washout = Yes, Capsule = Yes -->
            <EqualCondition DataElementId="capsule"
                ComparisonValue="yes"/>
            <EqualCondition DataElementId="thresholdgrowth"
                ComparisonValue="no"/>
        </AndCondition>
    </OrCondition>

```

```

<AndCondition>
  <EqualCondition DataElementId="washout"
    ComparisonValue="yes"/>
  <!-- Washout = Yes, Thresholdgrowth = Yes -->
  <EqualCondition DataElementId="capsule"
    ComparisonValue="no"/>
  <EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
  <EqualCondition DataElementId="washout"
    ComparisonValue="no"/>
  <!-- Capsule = Yes, Thresholdgrowth = Yes -->
  <EqualCondition DataElementId="capsule"
    ComparisonValue="yes"/>
  <EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
  <EqualCondition DataElementId="washout"
    ComparisonValue="yes"/>
  <!-- Washout = Yes, Capsule = Yes, Thresholdgrowth = Yes -->
  <EqualCondition DataElementId="capsule"
    ComparisonValue="yes"/>
  <EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc4Ep"/>
</Branch>
</DecisionPoint>
</Branch>
<Branch>
  <Label>10-19</Label>
  <!-- 10 <= Diameter <= 19 -->
  <AndCondition>
    <GreaterThanOrEqualsCondition DataElementId="diameter"
      ComparisonValue="diameterSmall"/>
    <LessThanOrEqualsCondition DataElementId="diameter"
      ComparisonValue="19"/>
  </AndCondition>
  <DecisionPoint>
    <Label>Washout/Capsule/Thresholdgrowth</Label>
    <Branch>
      <Label>None</Label>
      <!-- None / Zero Y's -->
      <AndCondition>
        <EqualCondition DataElementId="washout" ComparisonValue="no"/>
        <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
        <EqualCondition DataElementId="thresholdgrowth"
          ComparisonValue="no"/>
      </AndCondition>
    </Branch>
  </DecisionPoint>
</Branch>

```

```

        </AndCondition>
        <EndPointRef EndPointId="hcc3Ep"/>
    </Branch>
    <Branch>
        <Label>One</Label>
        <!-- One / One Y -->
        <OrCondition>
            <AndCondition>
                <EqualCondition DataElementId="washout"
                    ComparisonValue="yes"/>
                <!-- Washout = Yes -->
                <EqualCondition DataElementId="capsule"
                    ComparisonValue="no"/>
                <EqualCondition DataElementId="thresholdgrowth"
                    ComparisonValue="no"/>
            </AndCondition>
            <AndCondition>
                <EqualCondition DataElementId="washout"
                    ComparisonValue="no"/>
                <!-- Capsule = Yes -->
                <EqualCondition DataElementId="capsule"
                    ComparisonValue="yes"/>
                <EqualCondition DataElementId="thresholdgrowth"
                    ComparisonValue="no"/>
            </AndCondition>
            <AndCondition>
                <EqualCondition DataElementId="washout"
                    ComparisonValue="no"/>
                <!-- Thresholdgrowth = Yes -->
                <EqualCondition DataElementId="capsule"
                    ComparisonValue="no"/>
                <EqualCondition DataElementId="thresholdgrowth"
                    ComparisonValue="yes"/>
            </AndCondition>
        </OrCondition>
        <EndPointRef EndPointId="hcc4_5"/>
    </Branch>
    <Branch>
        <Label>Two or More</Label>
        <!-- Two / Two or more Y's -->
        <OrCondition>
            <AndCondition>
                <EqualCondition DataElementId="washout"
                    ComparisonValue="yes"/>
                <!-- Washout = Yes, Capsule = Yes -->
                <EqualCondition DataElementId="capsule"
                    ComparisonValue="yes"/>
                <EqualCondition DataElementId="thresholdgrowth"
                    ComparisonValue="no"/>
            </AndCondition>
            <AndCondition>

```

```

<EqualCondition DataElementId="washout"
    ComparisonValue="yes"/>
<!-- Washout = Yes, Thresholdgrowth = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="no"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="no"/>
    <!-- Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
    <!-- Washout = Yes, Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc5Ep"/>
</Branch>
</DecisionPoint>
</Branch>
<Branch>
    <Label>&gt;= 20</Label>
    <!-- Diameter >= 20 -->
    <GreaterThanOrEqualsCondition DataElementId="diameter"
        ComparisonValue="diameterLarge"/>
    <DecisionPoint>
        <Label>Washout/Capsule/Thresholdgrowth</Label>
        <Branch>
            <Label>None</Label>
            <!-- None / Zero Y's -->
            <AndCondition>
                <EqualCondition DataElementId="washout" ComparisonValue="no"/>
                <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
                <EqualCondition DataElementId="thresholdgrowth"
                    ComparisonValue="no"/>
            </AndCondition>
            <EndPointRef EndPointId="hcc4Ep"/>
        </Branch>
        <Branch>
            <Label>One</Label>

```

```

<!-- One / One Y -->
<OrCondition>
  <AndCondition>
    <EqualCondition DataElementId="washout"
      ComparisonValue="yes"/>
    <!-- Washout = Yes -->
    <EqualCondition DataElementId="capsule"
      ComparisonValue="no"/>
    <EqualCondition DataElementId="thresholdgrowth"
      ComparisonValue="no"/>
  </AndCondition>
  <AndCondition>
    <EqualCondition DataElementId="washout"
      ComparisonValue="no"/>
    <!-- Capsule = Yes -->
    <EqualCondition DataElementId="capsule"
      ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
      ComparisonValue="no"/>
  </AndCondition>
  <AndCondition>
    <EqualCondition DataElementId="washout"
      ComparisonValue="no"/>
    <!-- Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
      ComparisonValue="no"/>
    <EqualCondition DataElementId="thresholdgrowth"
      ComparisonValue="yes"/>
  </AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc5Ep"/>
</Branch>
<Branch>
  <Label>Two or More</Label>
  <!-- Two / Two or more Y's -->
  <OrCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
      <!-- Washout = Yes, Capsule = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
      <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="no"/>
    </AndCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
      <!-- Washout = Yes, Thresholdgrowth = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="no"/>
    </AndCondition>
  </OrCondition>
</Branch>

```

```

<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="no"/>
    <!-- Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
    <!-- Washout = Yes, Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc5Ep"/>
</Branch>
</DecisionPoint>
</Branch>
</DecisionPoint>
</Branch>
<Branch>
    <Label>Hypo/Iso-enhancing</Label>
    <!-- Hypo/Iso-enhancement -->
    <OrCondition>
        <EqualCondition DataElementId="arterialEnhancement"
            ComparisonValue="hypoEnhancing"/>
        <EqualCondition DataElementId="arterialEnhancement"
            ComparisonValue="isoEnhancing"/>
    </OrCondition>
    <DecisionPoint>
        <Label>Diameter</Label>
        <Branch>
            <Label>&lt; 20</Label>
            <!-- Diameter < 20 -->
            <LessThanCondition DataElementId="diameter"
                ComparisonValue="diameterLarge"/>
        <DecisionPoint>
            <Label>Washout/Capsule/Thresholdgrowth</Label>
            <Branch>
                <Label>None</Label>
                <!-- None / Zero Y's -->
                <AndCondition>
                    <EqualCondition DataElementId="washout" ComparisonValue="no"/>

```

```

<EqualCondition DataElementId="capsule" ComparisonValue="no"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="no"/>
</AndCondition>
<EndPointRef EndPointId="hcc3Ep"/>
</Branch>
<Branch>
<Label>One</Label>
<!-- One / One Y -->
<OrCondition>
<AndCondition>
<EqualCondition DataElementId="washout"
    ComparisonValue="yes"/>
<!-- Washout = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="no"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="no"/>
</AndCondition>
<AndCondition>
<EqualCondition DataElementId="washout"
    ComparisonValue="no"/>
<!-- Capsule = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="yes"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="no"/>
</AndCondition>
<AndCondition>
<EqualCondition DataElementId="washout"
    ComparisonValue="no"/>
<!-- Thresholdgrowth = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="no"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc3Ep"/>
</Branch>
<Branch>
<Label>Two or More</Label>
<!-- Two / Two or more Y's -->
<OrCondition>
<AndCondition>
<EqualCondition DataElementId="washout"
    ComparisonValue="yes"/>
<!-- Washout = Yes, Capsule = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="yes"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="no"/>

```

```

        ComparisonValue="no"/>
    </AndCondition>
    <AndCondition>
        <EqualCondition DataElementId="washout"
            ComparisonValue="yes"/>
        <!-- Washout = Yes, Thresholdgrowth = Yes -->
        <EqualCondition DataElementId="capsule"
            ComparisonValue="no"/>
        <EqualCondition DataElementId="thresholdgrowth"
            ComparisonValue="yes"/>
    </AndCondition>
    <AndCondition>
        <EqualCondition DataElementId="washout"
            ComparisonValue="no"/>
        <!-- Capsule = Yes, Thresholdgrowth = Yes -->
        <EqualCondition DataElementId="capsule"
            ComparisonValue="yes"/>
        <EqualCondition DataElementId="thresholdgrowth"
            ComparisonValue="yes"/>
    </AndCondition>
    <AndCondition>
        <EqualCondition DataElementId="washout"
            ComparisonValue="yes"/>
        <!-- Washout = Yes, Capsule = Yes, Thresholdgrowth = Yes -->
        <EqualCondition DataElementId="capsule"
            ComparisonValue="yes"/>
        <EqualCondition DataElementId="thresholdgrowth"
            ComparisonValue="yes"/>
    </AndCondition>
    </OrCondition>
    <EndPointRef EndPointId="hcc4Ep"/>
</Branch>
</DecisionPoint>
</Branch>
<Branch>
    <Label>&gt;= 20</Label>
    <!-- Diameter >= 20 -->
    <GreaterThanOrEqualsCondition DataElementId="diameter"
        ComparisonValue="diameterLarge"/>
<DecisionPoint>
    <Label>Washout/Capsule/Thresholdgrowth</Label>
    <Branch>
        <Label>None</Label>
        <!-- None / Zero Y's -->
        <AndCondition>
            <EqualCondition DataElementId="washout" ComparisonValue="no"/>
            <EqualCondition DataElementId="capsule" ComparisonValue="no"/>
            <EqualCondition DataElementId="thresholdgrowth"
                ComparisonValue="no"/>
        </AndCondition>
    </Branch>
    <EndPointRef EndPointId="hcc3Ep"/>

```

```
</Branch>
<Branch>
  <Label>One</Label>
  <!-- One / One Y -->
  <OrCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
      <!-- Washout = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="no"/>
      <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="no"/>
    </AndCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="no"/>
      <!-- Capsule = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
      <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="no"/>
    </AndCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="no"/>
      <!-- Thresholdgrowth = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="no"/>
      <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
    </AndCondition>
  </OrCondition>
  <EndPointRef EndPointId="hcc4Ep"/>
</Branch>
<Branch>
  <Label>Two or More</Label>
  <!-- Two / Two or more Y's -->
  <OrCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
      <!-- Washout = Yes, Capsule = Yes -->
      <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
      <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="no"/>
    </AndCondition>
    <AndCondition>
      <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
    </AndCondition>
  </OrCondition>
</Branch>
```

```

<!-- Washout = Yes, Thresholdgrowth = Yes -->
<EqualCondition DataElementId="capsule"
    ComparisonValue="no"/>
<EqualCondition DataElementId="thresholdgrowth"
    ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="no"/>
    <!-- Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
<AndCondition>
    <EqualCondition DataElementId="washout"
        ComparisonValue="yes"/>
    <!-- Washout = Yes, Capsule = Yes, Thresholdgrowth = Yes -->
    <EqualCondition DataElementId="capsule"
        ComparisonValue="yes"/>
    <EqualCondition DataElementId="thresholdgrowth"
        ComparisonValue="yes"/>
</AndCondition>
</OrCondition>
<EndPointRef EndPointId="hcc4Ep"/>
</Branch>
</DecisionPoint>
</Branch>
</DecisionPoint>
</Branch>
</DecisionPoint>
</Branch>
<Label>Adjust category</Label>
<AndCondition>
    <NotCondition>
        <EqualCondition DataElementId="adjustcategorybasedonAncillary"
            ComparisonValue="No"/>
    </NotCondition>
    <EqualCondition DataElementId="observationCharacter"
        ComparisonValue="notDefProbBenign"/>
</AndCondition>
<DecisionPoint>
    <Label>Adjust category</Label>
    <Branch>
        <EqualCondition DataElementId="adjustcategorybasedonAncillary"
            ComparisonValue="Upgradetohcc2"/>
        <EndPointRef EndPointId="hcc2Ep"/>
    </Branch>
    <Branch>

```

```

<EqualCondition DataElementId="adjustcategorybasedonAncillary"
    ComparisonValue="Upgradetohcc3"/>
<EndPointRef EndPointId="hcc3Ep"/>
</Branch>
<Branch>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary"
        ComparisonValue="Upgradetohcc4"/>
    <EndPointRef EndPointId="hcc4Ep"/>
</Branch>
<Branch>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary"
        ComparisonValue="Downgradetohcc4"/>
    <EndPointRef EndPointId="hcc4Ep"/>
</Branch>
<Branch>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary"
        ComparisonValue="Downgradetohcc3"/>
    <EndPointRef EndPointId="hcc3Ep"/>
</Branch>
<Branch>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary"
        ComparisonValue="Downgradetohcc2"/>
    <EndPointRef EndPointId="hcc2Ep"/>
</Branch>
<Branch>
    <EqualCondition DataElementId="adjustcategorybasedonAncillary"
        ComparisonValue="Downgradetohcc1"/>
    <EndPointRef EndPointId="hcc1Ep"/>
</Branch>
</DecisionPoint>
</Branch>
</DecisionPoint>
</Rules>

```

3.4 Endpoints

This section contains all the defined endpoints together with the reusable text fragments (TemplatePartial elements). Each EndPoint element specifies the report text to be inserted and other actions to be taken when the logic tree leads to a particular endpoint.

| # | Name | Data Type | Description / Usage |
|-----|--|-----------|---|
| 1 | TemplatePartial TemplatePartial elements define a reusable text fragment or macro that once defined can be repeatedly used in all endpoints. | | |
| 1.1 | id | xsd:id | Template partial identifier, which can be referred in the report text |

| | | | | | | | | | | | | | | |
|------------|--------------------------------------|---|---|----------------------|-----------|---|------------|--------------------------------------|-------------|---|------------|--------------------|--|--|
| | | Template definition includes the text mixed with the template elements as described below. | | | | | | | | | | | | |
| 1.2 | 1.2.1 | text | | | | | | | | | | | | |
| 1.2 | 2 | <p>InsertValue Insert the value of a Dataelement</p> <table border="1"> <tr> <td>1.2.2 .1.1</td><td>DataElementId</td><td>xsd:IDREF</td><td>The value of this Dataelement will be inserted</td></tr> <tr> <td>1.2.2 .1.2</td><td>SignificantDigits(optional)</td><td>xsd:integer</td><td>This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text.</td></tr> </table> | 1.2.2 .1.1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | 1.2.2 .1.2 | SignificantDigits (optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | | | | |
| 1.2.2 .1.1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | | | | | | | | | | | |
| 1.2.2 .1.2 | SignificantDigits (optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | | | | | | | | | | | |
| 1.2 | 2 | <p>InsertPartial Insert the contents of a TemplatePartial to be inserted</p> <table border="1"> <tr> <td>1.2.2 .2.1</td><td>PartialId</td><td>xsd:IDREF</td><td>The dynamic value of this TemplatePartial will be inserted.</td></tr> </table> | 1.2.2 .2.1 | PartialId | xsd:IDREF | The dynamic value of this TemplatePartial will be inserted. | | | | | | | | |
| 1.2.2 .2.1 | PartialId | xsd:IDREF | The dynamic value of this TemplatePartial will be inserted. | | | | | | | | | | | |
| 1.2 | 2.3 | <p>SectionIf Insert the contained template text if the given DataElement has any value.</p> <table border="1"> <tr> <td>1.2.2 .3.1</td><td>DataElementId</td><td>xsd:IDREF</td><td>Dataelement to be tested</td></tr> <tr> <td>1.2.2 .3.2</td><td>Recursive from 1.2</td><td></td><td></td></tr> </table> | 1.2.2 .3.1 | DataElementId | xsd:IDREF | Dataelement to be tested | 1.2.2 .3.2 | Recursive from 1.2 | | | | | | |
| 1.2.2 .3.1 | DataElementId | xsd:IDREF | Dataelement to be tested | | | | | | | | | | | |
| 1.2.2 .3.2 | Recursive from 1.2 | | | | | | | | | | | | | |
| 1.2 | 2.4 | <p>SectionIfValue Insert the contained template text if the given DataElement matches with the comparison value.</p> <table border="1"> <tr> <td>1.2.2 .4.1</td><td>DataElementId</td><td>xsd:IDREF</td><td>Dataelement to be tested</td></tr> <tr> <td>1.2.2 .4.2</td><td>ComparisonValue</td><td>xsd:token</td><td>Comparison value</td></tr> <tr> <td>1.2.2 .4.3</td><td>Recursive from 1.2</td><td></td><td></td></tr> </table> | 1.2.2 .4.1 | DataElementId | xsd:IDREF | Dataelement to be tested | 1.2.2 .4.2 | ComparisonValue | xsd:token | Comparison value | 1.2.2 .4.3 | Recursive from 1.2 | | |
| 1.2.2 .4.1 | DataElementId | xsd:IDREF | Dataelement to be tested | | | | | | | | | | | |
| 1.2.2 .4.2 | ComparisonValue | xsd:token | Comparison value | | | | | | | | | | | |
| 1.2.2 .4.3 | Recursive from 1.2 | | | | | | | | | | | | | |
| 1.2 | 2.5 | SectionIfNot Insert the contained template text if the given DataElement has no value. | | | | | | | | | | | | |

| | | | | | | |
|--|-------------|---|--------------------|--------------------|--------------------------|--------------------------|
| | | | 1.2.2 .5.1 | DataElementId | xsd:IDREF | Dataelement to be tested |
| | | | 1.2.2 .5.2 | Recursive from 1.2 | | |
| | 1.2. 2.6 | SectionIfValueNot Insert the contained template text if the given DataElement doesn't matches with the comparison value | | | | |
| | | 1.2.2 .6.1 | DataElementId | xsd:IDREF | Dataelement to be tested | |
| | | 1.2.2 .6.2 | ComparisonValue | xsd:token | Comparison value | |
| | | 1.2.2 .6.3 | Recursive from 1.2 | | | |

2 Endpoint

| | | | |
|-----|--|----------------------------|--|
| 2.1 | Id | xsd:ID | Endpoint identifier. This will be referred to be in the logic tree. |
| 2.2 | Label (optional) | text | Brief summary of the endpoints to be used in the documentation and in diagrams |
| 2.3 | Diagnosis (optional) can contain one or more diagnosis | | |
| | 2.3. 1.1 | CodingSystem (optional) | text |
| | 2.3. 1.2 | Code | xsd:token |
| | | | The source of coding system used. This should be a URL |
| | | | Code in coding system |
| 2.4 | ReportTexts Specifies blocks of text to be inserted in the report at various points. Can have one or more ReportText | | |
| | ReportText | | |
| | 2.4. 1 | SectionId | Specifies texts to be inserted at different points in the report. The supported sections are |

| | | | | | | | | | | | |
|-------------|------------------------------|---|---|---|-----------|---|-------------|------------------------------|-------------|---|--|
| | | | listed below | | | | | | | | |
| | 2.4. 1.1 | SectionId | <p style="color: red;">"findings" "impression" "recommendation" "impressionRecommendation" "citation"</p> | <p>Findings: Text to be inserted into the body of the report, typically at the point where the radiologist is currently working</p> <p>Impression: Text to be inserted into the impression section of the report, typically at the bottom of the report</p> <p>Recommendation: Text to be inserted into a recommendation section of a report, if applicable</p> <p>ImpressionRecommendation: When a recommendation section is not available, text which includes a recommendation to be inserted into the impression section of the report.</p> <p>Citation: Text to be added at the bottom of a report which provides citation information about the recommendations. See also the “Citation” tag in the Metadata section; the text in this tag should be inserted in place of that global citation when given for a particular EndPoint.</p> | | | | | | | |
| | 2.4. 2 | text | | | | | | | | | |
| | 2.4. 3 | <p>InsertValue Insert the value of a Dataelement</p> <table border="1"> <tr> <td>2.4.3 .1</td><td>DataElementId</td><td>xsd:IDREF</td><td>The value of this Dataelement will be inserted</td></tr> <tr> <td>2.4.3 .2</td><td>SignificantDigits(optional)</td><td>xsd:integer</td><td>This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text.</td></tr> </table> | 2.4.3 .1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | 2.4.3 .2 | SignificantDigits(optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | |
| 2.4.3 .1 | DataElementId | xsd:IDREF | The value of this Dataelement will be inserted | | | | | | | | |
| 2.4.3 .2 | SignificantDigits(optional) | xsd:integer | This is applicable if the DataElement referred is a NumericDataElement. This defines the number of decimal points can be inserted into the report text. | | | | | | | | |
| | 2.4. 4 | <p>InsertPartial Insert the contents of a TemplatePartial to be inserted</p> <table border="1"> <tr> <td>2.4.4 .1</td><td>PartialId</td><td>xsd:IDREF</td><td>The dynamic value of this TemplatePartial will be inserted.</td></tr> </table> | 2.4.4 .1 | PartialId | xsd:IDREF | The dynamic value of this TemplatePartial will be inserted. | | | | | |
| 2.4.4 .1 | PartialId | xsd:IDREF | The dynamic value of this TemplatePartial will be inserted. | | | | | | | | |

| | | | |
|------|---|---|--------------------------|
| | | | |
| 2.4. | SectionIf | | |
| 5 | Insert the contained template text if the given DataElement has any value. | | |
| | 2.4.5 | DataElementId | xsd:IDREF |
| | .1 | | Dataelement to be tested |
| | 2.4.5 | TextTemplateContent | |
| | .2 | Recursive, can contain TextTemplateContent itself | |
| 2.4. | SectionIfValue | | |
| 6 | Insert the contained template text if the given DataElement matches with the comparison value. | | |
| | 2.4.6 | DataElementId | xsd:IDREF |
| | .1 | | Dataelement to be tested |
| | 2.4.6 | ComparisonValue | xsd:token |
| | .2 | | Comparison value |
| | 2.4.6 | TextTemplateContent | |
| | .3 | Recursive, can contain TextTemplateContent itself | |
| 2.4. | SectionIfNot | | |
| 7 | Insert the contained template text if the given DataElement has no value. | | |
| | 2.4.7 | DataElementId | xsd:IDREF |
| | .1 | | Dataelement to be tested |
| | 2.4.7 | TextTemplateContent | |
| | .2 | Recursive, can contain TextTemplateContent itself | |
| 2.4. | SectionIfValueNot | | |
| 8 | Insert the contained template text if the given DataElement doesn't matches with the comparison value | | |
| | 2.4.8 | DataElementId | xsd:IDREF |
| | .1 | | Dataelement to be tested |
| | 2.4.8 | ComparisonValue | xsd:token |
| | .2 | | Comparison value |
| | 2.4.8 | TextTemplateContent | |
| | .3 | Recursive, can contain TextTemplateContent itself | |
| 2.5. | ActionableFinding (optional) | | |

| | | | | | | | | | | | | | | | | | |
|---------|--|---|--|--|--|---------|----------------------------|-----------|--|---------|-----------------------|------------|---|---------|-------------|--|---|
| | 2.5. | Category | text | | | | | | | | | | | | | | |
| | 1 | | | | | | | | | | | | | | | | |
| 2.6 | ImagingFollowup (optional) Specifies the parameters around recommended imaging follow-up | | | | | | | | | | | | | | | | |
| | 2.6.1 | ClinicalCondition | text | If the recommended follow-up has a clinical condition such as a patient has high risk for cancer | | | | | | | | | | | | | |
| | 2.6.2 | References (optional) Reference to the evidence base for the recommendation. Citation <table border="1"> <tr> <td>2.6.2.1</td><td>PubmedId (optional)</td><td>xsd:token</td><td>Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed</td></tr> <tr> <td>2.6.2.2</td><td>URI (optional)</td><td>xsd:anyURI</td><td>Any Reference URI (for e.g.: link to abstract on journal website)</td></tr> <tr> <td>2.6.2.3</td><td>Text</td><td></td><td>citation text (for e.g. : a bibliographic reference to the citation)</td></tr> </table> | | | | 2.6.2.1 | PubmedId (optional) | xsd:token | Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed | 2.6.2.2 | URI (optional) | xsd:anyURI | Any Reference URI (for e.g.: link to abstract on journal website) | 2.6.2.3 | Text | | citation text (for e.g. : a bibliographic reference to the citation) |
| 2.6.2.1 | PubmedId (optional) | xsd:token | Pubmed reference Identifier https://www.ncbi.nlm.nih.gov/pubmed | | | | | | | | | | | | | | |
| 2.6.2.2 | URI (optional) | xsd:anyURI | Any Reference URI (for e.g.: link to abstract on journal website) | | | | | | | | | | | | | | |
| 2.6.2.3 | Text | | citation text (for e.g. : a bibliographic reference to the citation) | | | | | | | | | | | | | | |
| | 2.6.3 | EvidenceLevel Contains information to encode the strength of the evidence behind the recommendation | | | | | | | | | | | | | | | |
| | 2.6.3.1 | CodingSystem | text | The source of coding system used. This should be a URL | | | | | | | | | | | | | |
| | 2.6.3.2 | Code | xsd:token | Code in coding system | | | | | | | | | | | | | |
| | 2.6.3.3 | xsd:token | | | | | | | | | | | | | | | |
| | 2.6.4 | PreferredImagingExam For the recommended imaging follow-up, the exam that would be the first choice. | | | | | | | | | | | | | | | |
| | 2.6.4.1 | CodingSystem (optional) | text | The source of coding system used. This should be a URL | | | | | | | | | | | | | |
| | | Code | xsd:token | Code in coding system | | | | | | | | | | | | | |
| | 2.6.5 | AcceptableImagingExams For the recommended imaging follow-up the other exams that would satisfy the recommendation. | | | | | | | | | | | | | | | |

| Exam | | | | |
|------|----------------------------|--|---|---|
| 2.6. | code 5.1 | text | Code in coding system | |
| 2.6. | CodeSystem 5.2 | text | The source of coding system used. This should be a URL | |
| 2.6. | Modality 5.3 | text | modality | |
| 2.6. | BodyRegion 5.4 | text | Body region | |
| 2.6. | text 5.5 | | | |
| 2.6. | IndicationForFollowup 6 | The encoding of the indication or reason for the follow-up imaging exam. | | |
| | 2.6.6.1 | CodingSystem (optional) | text | The source of coding system used. This should be a URL |
| | 2.6.6.2 | Code | xsd:token | Code in coding system |
| | 2.6.6.3 | text | | |
| 2.6. | RecommendedTimeFrame 7 | Recommended time frame for the preferred next exam. | | |
| | 2.6. | Earliest 7.1 | Xsd:duration | Earliest time relative to the exam date time. Following is the example to mention the earliest time based on xsd:duration definition “P5Y2M10DT15H” |
| | 2.6. | Latest 7.2 | Xsd:duration | Latest time relative to the exam date time. Following is the example to mention the latest time based on xsd:duration definition “P5Y2M10DT15H” |
| | 2.6. | empty 7.3 | | |

3.4.1 Sample

```
<EndPoint Id="ID000">
  <Label>Label0</Label>
  <Diagnosis CodingSystem="CodingSystem0" Code="Code0">
```

```

</Diagnosis>
<ReportTexts>
  <ReportText SectionId="findings">
    <SectionIf DataElementId="ID000">
    </SectionIf>
    <SectionIfValueNot DataElementId="ID000" ComparisonValue="ComparisonValue0">
    </SectionIfValueNot>
  </ReportText>
  <ReportText SectionId="findings">
    <SectionIfValue DataElementId="ID000" ComparisonValue="ComparisonValue1">
    </SectionIfValue>
    <InsertValue DataElementId="ID000" SignificantDigits="0"/>
  </ReportText>
  <ReportText SectionId="findings">
    <InsertValue DataElementId="ID000" SignificantDigits="0"/>
    <InsertValue DataElementId="ID000" SignificantDigits="0"/>
  </ReportText>
  <ReportText SectionId="findings">
    <SectionIfNot DataElementId="ID000">
    </SectionIfNot>
    <InsertValue DataElementId="ID000" SignificantDigits="0"/>
  </ReportText>
</ReportTexts>
<ActionableFinding Category="Category0"/>
<ImagingFollowup>
  <Exam Code="Code1" CodeSystem="CodeSystem0" Modality="Modality0" BodyRegion="BodyRegion0">
  </Exam>
  <Exam Code="Code2" CodeSystem="CodeSystem1" Modality="Modality1" BodyRegion="BodyRegion1">
  </Exam>
</ImagingFollowup>
</EndPoint>

```

3.4.2 Real-world Sample

```

<EndPoints>
  <TemplatePartial Id="adjustcategorytext">
    <SectionIfValueNot DataElementId="adjustcategorybasedonAncillary" ComparisonValue="No">
      <SectionIf DataElementId="ancillaryFavoringMalignancy"> HCC category has been adjusted
        based on the selected Ancillary features favoring Malignancy <InsertValue
          DataElementId="ancillaryFavoringMalignancy"/>
      </SectionIf>
      <SectionIf DataElementId="ancillaryFavoringBenignity"> HCC category has been adjusted
        based on the selected Ancillary features favoring Benignity <InsertValue
          DataElementId="ancillaryFavoringBenignity"/>
      </SectionIf>
    </SectionIfValueNot>
  </TemplatePartial>
  <EndPoint Id="hcc1Ep">
    <Label>HCC-1</Label>
    <ReportTexts>
      <ReportText SectionId="findings">[HCC-1] Imaging features diagnostic of a benign entity

```

```
or definite spontaneous disappearance at follow up. <InsertPartial  
    PartialId="adjustcategorytext"/>  
  </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hcc2Ep">  
  <Label>HCC-2</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-2] Observation with imaging features suggestive  
      but not diagnostic of a benign entity. <InsertPartial PartialId="adjustcategorytext"  
      />  
    </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hcc3Ep">  
  <Label>HCC-3</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-3] Observation that does not meet unequivocal  
      criteria for other LI-RADS categories. <InsertPartial PartialId="adjustcategorytext"  
      />  
    </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hcc4Ep">  
  <Label>HCC-4</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-4] Observation with imaging features suggestive  
      but not diagnostic of HCC. <InsertPartial PartialId="adjustcategorytext"/>  
    </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hcc5Ep">  
  <Label>HCC-5</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-5] Observation with imaging features diagnostic of  
      HCC. <InsertPartial PartialId="adjustcategorytext"/>  
    </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hcc5vEp">  
  <Label>HCC-5V</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-5V] Presence of tumor in vein lumen.  
      <InsertPartial PartialId="adjustcategorytext"/>  
    </ReportText>  
  </ReportTexts>  
</EndPoint>  
<EndPoint Id="hccmEp">  
  <Label>HCC-M</Label>  
  <ReportTexts>  
    <ReportText SectionId="findings">[HCC-M] Observation with one or more imaging features
```

```
        that favor non-HCC malignancy <InsertPartial PartialId="adjustcategorytext"/>
    </ReportText>
</ReportTexts>
</EndPoint>
<EndPoint Id="hcctreatedEp">
    <Label>HCC-Treated</Label>
    <ReportTexts>
        <ReportText SectionId="findings">[HCC-Treated] An observation that has undergone
            loco-regional treatment. </ReportText>
    </ReportTexts>
</EndPoint>
<EndPoint Id="hcc4_5">
    <Label>HCC-4/HCC-5</Label>
    <ReportTexts>
        <ReportText SectionId="findings">[HCC-4/HCC-5] Refers to a cell in the LI-RADS table
            where observations may be considered LR-4, LR-5us, or LR-5g <InsertPartial
                PartialId="adjustcategorytext"/>
        </ReportText>
    </ReportTexts>
</EndPoint>
</EndPoints>
```